

Report on a Helicopter-Borne AeroTEM System Electromagnetic & Magnetic Survey



Aeroquest Job # 08-054

ShIPLEY Block

Gogama area, Northern Ontario
NTS 041010

For



by



7687 Bath Road,
Mississauga, ON, L4T 3T1
Tel: (905) 672-9129
Fax: (905) 672-7083
www.aeroquest.ca

Report date: April 2008

Report on a Helicopter-Borne AeroTEM System Electromagnetic & Magnetic Survey

Aeroquest Job # 08-054

Shipley Block

Gogama area, Northern Ontario
NTS 041010

For



129 Fielding Road
Lively, Ontario
P3Y 1L7
Phone: 705-682-9297
Fax: 705-682-2144
www.wallbridgeminig.com

By



7687 Bath Road,
Mississauga, ON, L4T 3T1
Tel: (905) 672-9129
Fax: (905) 672-7083
www.aeroquest.ca

Report date: April 2008



TABLE OF CONTENTS

TABLE OF CONTENTS	i
LIST OF FIGURES.....	2
LIST OF MAPS SCALE (1:20000)	2
1. INTRODUCTION.....	3
2. SURVEY AREA.....	3
3. SURVEY SPECIFICATIONS AND PROCEDURES	4
3.1. Navigation	5
3.2. System Drift.....	5
3.3. Field QA/QC Procedures	5
4. AIRCRAFT AND EQUIPMENT	5
4.1. Aircraft	5
4.2. Magnetometer	6
4.3. Electromagnetic System	6
4.4. AeroDAS Acquisition System	7
4.5. RMS DGR-33 Acquisition System	8
4.6. Magnetometer Base Station	9
4.7. Radar Altimeter.....	10
4.8. Video Tracking and Recording System.....	10
4.9. GPS Navigation System	10
4.10. Digital Acquisition System	10
5. PERSONNEL	11
6. DELIVERABLES	11
6.1. Hardcopy Deliverables	11
6.2. Digital Deliverables.....	11
6.2.1. Final Database of Survey Data (.GDB, .XYZ).....	11
6.2.2. Geosoft Grid files (.GRD) and Tiff Images (.tif).....	12
6.2.3. Digital Versions of Final Maps (.MAP, .PDF).....	12
6.2.4. Google Earth Survey Files (.kmz).....	12
6.2.5. Free Viewing Software (.EXE).....	12
6.2.6. Digital Copy of this Document (.PDF).....	12
7. DATA PROCESSING AND PRESENTATION	12
7.1. Base Map.....	12
7.2. Flight Path & Terrain Clearance	13
7.3. Electromagnetic Data	13
7.4. Magnetic Data.....	13
8. General Comments	14
8.1. Magnetic Response	14
8.2. EM Anomalies	14
APPENDIX 1: Survey Boundaries	17

APPENDIX 2: Mining Claims.....	18
APPENDIX 3: AeroTEM Anomaly Listing.....	19
APPENDIX 4: Description of Database Fields	22
APPENDIX 5: AeroTEM Design Considerations	23
APPENDIX 6: AeroTEM Instrumentation Specification Sheet	29

LIST OF FIGURES

Figure 1. Project Area	3
Figure 2. Project flight path and mining claims.....	4
Figure 3. Helicopter of the type used for survey.....	6
Figure 4. The magnetometer bird (A) and AeroTEM III EM bird (B).....	7
Figure 5. Schematic of Transmitter and Receiver waveforms.....	7
Figure 6. AeroTEM III Instrument Rack.....	9
Figure 7. Digital video camera typical mounting location	10
Figure 8. AeroTEM response to a ‘thin’ vertical conductor.....	15
Figure 9. AeroTEM response for a ‘thick’ vertical conductor.....	15
Figure 10. AeroTEM response over a ‘thin’ dipping conductor.....	16

LIST OF MAPS SCALE (1:20000)

- TMI – Coloured Total Magnetic Intensity (TMI) with line contours EM anomaly symbols.
- ZOFF0 – AeroTEM Z0 Off-time with line contours and EM anomaly symbols.
- EM – AeroTEM off-time profiles Z3 – Z15 EM anomaly symbols.

1. INTRODUCTION

This report describes a helicopter-borne geophysical survey carried out on behalf of Wallbridge Mining Company Ltd. on their Shipley Block, Gogama area, Northern Ontario.

The principal geophysical sensor is Aeroquest's exclusive AeroTEM III ('November' System) time domain helicopter electromagnetic system which is employed in conjunction with a high-sensitivity caesium vapour magnetometer. Ancillary equipment includes a real-time differential GPS navigation system, radar altimeter, video recorder, and a base station magnetometer. Full-waveform streaming EM data is recorded at 36,000 samples per second. The streaming data comprise the transmitted waveform, and the X component and Z component of the resultant field at the receivers. A secondary acquisition system (RMS) records the ancillary data.

The total survey coverage is 443.4 km, of which 423.2 line-km fell within the defined project area (Appendix 1). The survey was flown at 200 metres line spacing, with an area of 100 m spacing in the western part of the block. Flight direction was N-S (0°). The survey flying described in this report took place between January 31st and February 6th, 2008. This report describes the survey logistics, the data processing, presentation, and provides a brief overview of the results.

2. SURVEY AREA

The Project area (Figure 1) is located in Northern Ontario 175 km northwest of Sudbury and 175 km northeast of Sault Ste. Marie. It is made up of a single block, Shipley (67.1) over low lying terrain with a number of lakes and rivers. Elevations ranged from approx 400 – 550 m above sea level. The survey covers either wholly or partially 36 mining claims, details of which are in Appendix 2.

The base of survey operations and crew accommodation was in Gogama.



Figure 1. Project Area




Figure 2. Project flight path and mining claims

3. SURVEY SPECIFICATIONS AND PROCEDURES

The survey specifications are summarised in the following table:

Project Name	Line Spacing (metres)	Line Direction	Survey Coverage (line-km)	Dates flown
Shipley	100 / 200	N-S (0°)	443.4	Jan 31 – Feb 06, 2008

Table 1. Survey specifications summary

The survey coverage was calculated by adding up the along-line distance of the survey lines and control (tie) lines as presented in the final Geosoft database. The survey was flown with a line spacing of 100 and 200 metres. The control (tie) lines were flown perpendicular to the survey lines with a spacing of 2000 metres.

The nominal EM bird terrain clearance is 30 metres, but can be higher in more rugged terrain due to safety considerations and the capabilities of the aircraft. The magnetometer sensor is mounted in a smaller bird connected to the tow rope 32 metres above the EM bird and 21 metres below the helicopter (Figure 4). Nominal survey speed over relatively flat terrain is 75 km/hr and is generally lower in rougher terrain. Scan rates for ancillary data acquisition is 0.1 second for the magnetometer and altimeter, and 0.2 second for the GPS determined position. The EM data is acquired as a data stream at a sampling rate of 36,000 samples per second and

is processed to generate final data at 10 samples per second. The 10 samples per second translate to a geophysical reading about every 1.5 to 2.5 metres along the flight path.

3.1. NAVIGATION

Navigation is carried out using a GPS receiver, an AGNAV2 system for navigation control, and an RMS DGR-33 data acquisition system which records the GPS coordinates. The x-y-z position of the aircraft, as reported by the GPS, is recorded at 0.2 second intervals. The system has a published accuracy of less than 3 metres. A recent static ground test of the Mid-Tech WAAS GPS yielded a standard deviation in x and y of under 0.6 metres and for z under 1.5 metres over a two-hour period.

3.2. SYSTEM DRIFT

Unlike frequency domain electromagnetic systems, the AeroTEM III system has negligible drift due to thermal expansion. The operator is responsible for ensuring the instrument is properly warmed up prior to departure and that the instruments are operated properly throughout the flight. The operator maintains a detailed flight log during the survey noting the times of the flight and any unusual geophysical or topographic features. Each flight included at least two high elevation 'background' checks. During the high elevation checks, an internal 5 second wide calibration pulse in all EM channels was generated in order to ensure that the gain of the system remained constant and within specifications.

3.3. FIELD QA/QC PROCEDURES

On return of the pilot and operator to the base, usually after each flight, the AeroDAS streaming EM data and the RMS data are carried on removable hard drives and FlashCards, respectively and transferred to the data processing work station. At the end of each day, the base station magnetometer data on FlashCard is retrieved from the base station unit.

Data verification and quality control includes a comparison of the acquired GPS data with the flight plan; verification and conversion of the RMS data to an ASCII format XYZ data file; verification of the base station magnetometer data and conversion to ASCII format XYZ data; and loading, processing and conversion of the streaming EM data from the removable hard drive. All data is then merged to an ASCII XYZ format file which is then imported to an Oasis database for further QA/QC and for the production of preliminary EM, magnetic contour, and flight path maps.

Survey lines which show excessive deviation from the intended flight path are re-flown. Any line or portion of a line on which the data quality did not meet the contract specification was noted and reflown.

4. AIRCRAFT AND EQUIPMENT

4.1. AIRCRAFT

A Eurocopter (Aerospatiale) AS350 BA "A-Star" helicopter - registration C-GJIX was used as survey platform. The helicopter was owned and operated by Questral Helicopters, Ottawa. Installation of the geophysical and ancillary equipment was carried out by Aeroquest Limited personnel in conjunction with a licensed aircraft engineer. The survey aircraft was flown at a nominal terrain clearance of 220 ft (65 metres).



Figure 3. Helicopter of the type used for survey

4.2. MAGNETOMETER

The Aeroquest airborne survey system employs the Geometrics G-823A caesium vapour magnetometer sensor installed in a two metre towed bird airfoil attached to the main tow line, 17 metres below the helicopter (Figure 4). The sensitivity of the magnetometer is 0.001 nanoTesla at a 0.1 second sampling rate. The nominal ground clearance of the magnetometer bird is 51 metres (170 ft.). The magnetic data is recorded at 10 Hz by the RMS DGR-33.

4.3. ELECTROMAGNETIC SYSTEM

The electromagnetic system is an Aeroquest AeroTEM III time domain towed-bird system (Figure 4). The current AeroTEM III transmitter dipole moment is from 183 kNIA. The AeroTEM bird is towed 53 metres (175 ft) below the helicopter. More technical details of the system may be found in Appendix 4.

The wave-form is triangular with a symmetric transmitter on-time pulse of 1250 μ s and a base frequency of 90 Hz (Figure 5). The current alternates polarity every on-time pulse. During every Tx on-off cycle (200 per second), 120 contiguous channels of raw X and Z component (and a transmitter current monitor, itx) of the received waveform are measured. The channel time widths are defined in Section 4.4 below. This 120 channel data is referred to as the raw streaming data. The AeroTEM system has two separate EM data recording streams, the conventional RMS DGR-33 and the AeroDAS system which records the full waveform (Figure 5).




Figure 4. The magnetometer bird (A) and AeroTEM III EM bird (B)




Figure 5. Schematic of Transmitter and Receiver waveforms

4.4. AERODAS ACQUISITION SYSTEM

The 120 channels of raw streaming data are recorded by the AeroDAS acquisition system (Figure 6) onto a removable hard drive. The streaming data are processed post-survey to yield 33 stacked and binned on-time and off-time channels at a 10 Hz sample rate. The timing of the final processed EM channels is described in the following table:



Average TxOn -18.1556 us
 Average TxSwitch 895.0634 us
 Average TxOff 1734.3457 us

Channel	Sample Range	Time Width (us)	Time Center (us)	Time After TxOn (us)
On1	4 - 4	27.778	97.222	115.378
On2	5 - 5	27.778	125.000	143.156
On3	6 - 6	27.778	152.778	170.933
On4	7 - 7	27.778	180.556	198.711
On5	8 - 8	27.778	208.333	226.489
On6	9 - 9	27.778	236.111	254.267
On7	10 - 10	27.778	263.889	282.044
On8	11 - 11	27.778	291.667	309.822
On9	12 - 12	27.778	319.444	337.600
On10	13 - 13	27.778	347.222	365.378
On11	14 - 14	27.778	375.000	393.156
On12	15 - 15	27.778	402.778	420.933
On13	16 - 16	27.778	430.556	448.711
On14	17 - 17	27.778	458.333	476.489
On15	18 - 18	27.778	486.111	504.267
On16	19 - 19	27.778	513.889	532.044

Channel	Sample Range	Time Width (us)	Time Center (us)	Time After TxOff (us)
Off0	67 - 67	27.778	1847.222	112.877
Off1	68 - 68	27.778	1875.000	140.654
Off2	69 - 69	27.778	1902.778	168.432
Off3	70 - 70	27.778	1930.556	196.210
Off4	71 - 71	27.778	1958.333	223.988
Off5	72 - 72	27.778	1986.111	251.765
Off6	73 - 75	83.333	2041.667	307.321
Off7	76 - 78	83.333	2125.000	390.654
Off8	79 - 81	83.333	2208.333	473.988
Off9	82 - 84	83.333	2291.667	557.321
Off10	85 - 89	138.889	2402.778	668.432
Off11	90 - 94	138.889	2541.667	807.321
Off12	95 - 101	194.444	2708.333	973.988
Off13	102 - 111	277.778	2944.444	1210.099
Off14	112 - 126	416.667	3291.667	1557.321
Off15	127 - 149	638.889	3819.444	2085.099
Off16	150 - 185	1000.000	4638.889	2904.543

4.5. RMS DGR-33 ACQUISITION SYSTEM

In addition to the magnetics, altimeter and position data, six channels of real time processed off-time EM decay in the Z direction and one in the X direction are recorded by the RMS DGR-33 acquisition system at 10 samples per second and plotted real-time on the analogue chart recorder. These channels are derived by a binning, stacking and filtering procedure on the raw streaming data. The primary use of the RMS EM data (Z1 to Z6, X1) is to provide for real-time QA/QC on board the aircraft.

The channel window timing of the RMS DGR-33 6 channel system is described in the table below.

RMS Channel	Start time (µs)	End time (µs)	Width (µs)	Streaming Channels
Z1, X1	1269.8	1322.8	52.9	48-50
Z2	1322.8	1455.0	132.2	50-54
Z3	1428.6	1587.3	158.7	54-59
Z4	1587.3	1746.0	158.7	60-65
Z5	1746.0	2063.5	317.5	66-77
Z6	2063.5	2698.4	634.9	78-101



Figure 6. AeroTEM III Instrument Rack

4.6. MAGNETOMETER BASE STATION

The base magnetometer was a Geometrics G-859 caesium vapour magnetometer system with integrated GPS. Data logging and UTC time synchronisation was carried out within the magnetometer, with the GPS providing the timing signal. The data logging was configured to measure at 1.0 second intervals. Digital recording resolution was 0.001 nT. The sensor was placed on a tripod in an area of low magnetic gradient and free of cultural noise sources. A continuously updated display of the base station values was available for viewing and regularly monitored to ensure acceptable data quality and diurnal variation.

4.7. RADAR ALTIMETER

A Terra TRA 3500/TRI-30 radar altimeter is used to record terrain clearance. The antenna was mounted on the outside of the helicopter beneath the cockpit. Therefore, the recorded data reflect the height of the helicopter above the ground. The Terra altimeter has an altitude accuracy of +/- 1.5 metres.

4.8. VIDEO TRACKING AND RECORDING SYSTEM

A high resolution digital colour 8 mm video camera is used to record the helicopter ground flight path along the survey lines. The video is digitally annotated with GPS position and time and can be used to verify ground positioning information and cultural causes of anomalous geophysical responses.



Figure 7. Digital video camera typical mounting location

4.9. GPS NAVIGATION SYSTEM

The navigation system consists of an Ag-Nav Incorporated AG-NAV2 GPS navigation system comprising a PC-based acquisition system, navigation software, a deviation indicator in front of the aircraft pilot to direct the flight, a full screen display with controls in front of the operator, a Mid-Tech RX400p WAAS-enabled GPS receiver mounted on the instrument rack and an antenna mounted on the magnetometer bird. WAAS (Wide Area Augmentation System) consists of approximately 25 ground reference stations positioned across the United States that monitor GPS satellite data. Two master stations located on the east and west coasts collect data from the reference stations and create a GPS correction message. This correction accounts for GPS satellite orbit and clock drift plus signal delays caused by the atmosphere and ionosphere. The corrected differential message is then broadcast through one of two geostationary satellites, or satellites with a fixed position over the equator. The corrected position has a published accuracy of less than 3 metres.

Survey co-ordinates are set up prior to the survey and the information is fed into the airborne navigation system. The co-ordinate system employed in the survey design was WGS84 [World] using the UTM zone 17N projection. The real-time differentially corrected GPS positional data was recorded by the RMS DGR-33 in geodetic coordinates (latitude and longitude using WGS84) at 0.2 s intervals.

4.10. DIGITAL ACQUISITION SYSTEM

The AeroTEM received waveform sampled during on and off-time at 120 channels per decay, 300 times per second, was logged by the proprietary AeroDAS data acquisition system. The

channel sampling commences at the start of the Tx cycle and the width of each channel is 27.78 seconds. The streaming data was recorded on a removable hard-drive and was later backed-up onto DVD-ROM from the field-processing computer.

The RMS Instruments DGR33A data acquisition system was used to collect and record the analogue data stream, i.e. the positional and secondary geophysical data, including processed 6 channel EM, magnetics, radar altimeter, GPS position, and time. The data was recorded on 128 Mb capacity FlashCard. The RMS output was also directed to a thermal chart recorder.

5. PERSONNEL

The following Aeroquest personnel were involved in the project:

- Manager of Operations: Bert Simon
- Manager of Data Processing: Gord Smith
- Field Data Processor: Ericka Solano, Chris Kahue
- Field Operator: Ioan Serbu, Doug Spence
- Data Interpretation and Reporting: Gord Smith, Marion Bishop

The survey pilots, Mat Ritchie and Gerhard Geertsema, were employed directly by the helicopter operator – Questral Helicopters.

6. DELIVERABLES

6.1. HARDCOPY DELIVERABLES

The report includes a set of three 1:20,000 maps. The survey area is covered by a single map plate and three geophysical data products are delivered as listed below:

- TMI – Coloured Total Magnetic Intensity (TMI) with line contours and EM anomaly symbols.
- ZOFF0 – AeroTEM Z0 Off-time with line contours and EM anomaly symbols.
- EM – AeroTEM off-time profiles Z3 – Z15 and EM anomaly symbols.

The coordinate/projection system for the maps is NAD83 – UTM Zone 17N. For reference, the latitude and longitude in WGS84 are also noted on the maps.

All the maps show flight path trace, skeletal topography, and conductor picks represented by an anomaly symbol classified according to calculated on-time conductance. The anomaly symbol is accompanied by postings denoting the calculated off-time conductance, a thick or thin classification and an anomaly identifier label. The anomaly symbol legend is given in the margin of the maps. The magnetic field data is presented as superimposed line contours with a minimum contour interval of 10 nT.

6.2. DIGITAL DELIVERABLES

6.2.1. Final Database of Survey Data (.GDB, .XYZ)

The geophysical profile data is archived digitally in a Geosoft GDB binary format database. A description of the contents of the individual channels in the database can be found in Appendix 2. A copy of this digital data is archived at the Aeroquest head office in Mississauga.

6.2.2. Geosoft Grid files (.GRD) and Tiff Images (.tif)

Levelled Grid products used to generate the geophysical map images. Cell size for all grid files is 10 metres.

- Total Magnetic Intensity (MagU)
- AeroTEM Z Offtime Channel 1 (ZOFF0)

6.2.3. Digital Versions of Final Maps (.MAP, .PDF)

Map files in Geosoft .map and Adobe PDF format.

6.2.4. Google Earth Survey Files (.kmz)

Flight navigation lines, EM anomalies, geophysical grids in Google earth KMZ format. Double click to view flight lines in Google Earth.

6.2.5. Free Viewing Software (.EXE)

- Geosoft Oasis Montaj Viewing Software
- Adobe Acrobat Reader
- Google Earth Viewer

6.2.6. Digital Copy of this Document (.PDF)

Adobe PDF format of this document.

7. DATA PROCESSING AND PRESENTATION

All in-field and post-field data processing was carried out using Aeroquest proprietary data processing software and Geosoft Oasis Montaj software. Maps were generated using 36-inch wide Hewlett Packard ink-jet plotters.

7.1. BASE MAP

The geophysical maps accompanying this report are based on positioning in the NAD827 datum. The survey geodetic GPS positions have been projected using the Universal Transverse Mercator projection in Zone 17 North. A summary of the map datum and projection specifications is given following:

- Ellipse: GRS 1980
- Ellipse major axis: 6378137m eccentricity: 0.081819191
- Datum: North American 1983 - Canada Mean
- Datum Shifts (x,y,z) : 0, 0, 0 metres
- Map Projection: Universal Transverse Mercator Zone 17 (Central Meridian 87°W)
- Central Scale Factor: 0.9996
- False Easting, Northing: 500,000m, 0m

For reference, the latitude and longitude in WGS84 are also noted on the maps.

The background vector topography was derived from Natural Resources Canada 1:50000 National Topographic Database data and the background shading were derived from NASA Shuttle Radar Topography Mission (SRTM) 90 metres resolution DEM data.

7.2. FLIGHT PATH & TERRAIN CLEARANCE

The position of the survey helicopter was directed by use of the Global Positioning System (GPS). Positions were updated five times per second (5 Hz) and expressed as WGS84 latitude and longitude calculated from the raw pseudo range derived from the C/A code signal. The instantaneous GPS flight path, after conversion to UTM co-ordinates, is drawn using linear interpolation between the x/y positions. The terrain clearance was maintained with reference to the radar altimeter. The raw Digital Terrain Model (DTM) was derived by taking the GPS survey elevation and subtracting the radar altimeter terrain clearance values. The calculated topography elevation values are relative and are not tied in to surveyed geodetic heights.

Each flight included at least two high elevation ‘background’ checks. These high elevation checks are to ensure that the gain of the system remained constant and within specifications.

7.3. ELECTROMAGNETIC DATA

The raw streaming data, sampled at a rate of 36,000 Hz (120 channels, 300 times per second) was reprocessed using a proprietary software algorithm developed and owned by Aeroquest Limited. Processing involves the compensation of the X and Z component data for the primary field waveform. Coefficients for this compensation for the system transient are determined and applied to the stream data. The stream data are then pre-filtered, stacked, binned to the 33 on and off-time channels and checked for the effectiveness of the compensation and stacking processes. The stacked data is then filtered, levelled and split up into the individual line segments. Further base level adjustments may be carried out at this stage.

The final field processing step was to merge the processed EM data with the other data sets into a Geosoft GDB file. The EM fiducial is used to synchronize the two datasets. The processed channels are merged into ‘array format; channels in the final Geosoft database as Zon, Zoff, Xon, and Xoff

The filtering of the stacked data is designed to remove or minimize high frequency noise that can not be sourced from the geology. Apparent bedrock EM anomalies were interpreted with the aid of an auto-pick from positive peaks and troughs in the on-time Z channel responses correlated with X channel responses. The auto-picked anomalies were reviewed and edited by a geophysicist on a line by line basis to discriminate between thin and thick conductor types. Anomaly picks locations were migrated and removed as required. This process ensures the optimal representation of the conductor centres on the maps.

At each conductor pick, estimates of the off-time conductance have been generated based on a horizontal plate source model for those data points along the line where the response amplitude is sufficient to yield an acceptable estimate. Some of the EM anomaly picks do not display a Tau value; this is due to the inability to properly define the decay of the conductor usually because of low signal amplitudes. Each conductor pick was then classified according to a set of seven ranges of calculated off-time conductance values. For high conductance sources, the on-time conductance values may be used, since it provides a more accurate measure of high-conductance sources. Each symbol is also given an identification letter label, unique to each flight line. Conductor picks that did not yield an acceptable estimate of off-time conductance due to a low amplitude response were classified as a low conductance source. Please refer to the anomaly symbol legend located in the margin of the maps.

7.4. MAGNETIC DATA

Prior to any levelling the magnetic data was subjected to a lag correction of -0.1 seconds and a spike removal filter. The filtered aeromagnetic data were then corrected for diurnal

variations using the magnetic base station and the intersections of the tie lines. No corrections for the regional reference field (IGRF) were applied. The corrected profile data were interpolated on to a grid using bi-directional gridding with a grid cell size of 20 metres. The final levelled grid provided the basis for threading the presented contours which have a minimum contour interval of 10 nT.

8. GENERAL COMMENTS

The survey was successful in mapping the magnetic and conductive properties of the geology throughout the survey area. Below is a brief interpretation of the results. For a detailed interpretation please contact Aeroquest Limited.

8.1. MAGNETIC RESPONSE

The magnetic data provide a high resolution map of the distribution of the magnetic mineral content of the survey area. This data can be used to interpret the location of geological contacts and other structural features such as faults and zones of magnetic alteration. The sources for anomalous magnetic responses are generally thought to be predominantly magnetite because of the relative abundance and strength of response (high magnetic susceptibility) of magnetite over other magnetic minerals such as pyrrhotite.

8.2. EM ANOMALIES

The EM anomalies on the maps are classified by conductance (as described earlier in the report) and also by the thickness of the source. A thin, vertically orientated source produces a double peak anomaly in the z-component response and a positive to negative crossover in the x-component response (Figure 8). For a vertically orientated thick source (say, greater than 10 metres), the response is a single peak in the z-component response and a negative to positive crossover in the x-component response (Figure 9). Because of these differing responses, the AeroTEM system provides discrimination of thin and thick sources and this distinction is indicated on the EM anomaly symbols (N = thin and K = thick). Where multiple, closely spaced conductive sources occur, or where the source has a shallow dip, it can be difficult to uniquely determine the type (thick vs. thin) of the source (Figure 10). In these cases both possible source types may be indicated by picking both thick and thin response styles. For shallow dipping conductors the 'thin' pick will be located over the edge of the source, whereas the 'thick' pick will fall over the downdip 'heart' of the anomaly.




Figure 8. AeroTEM response to a 'thin' vertical conductor




Figure 9. AeroTEM response for a 'thick' vertical conductor




Figure 10. AeroTEM response over a 'thin' dipping conductor

All cases should be considered when analyzing the interpreted picks and prioritizing for follow-up. Specific anomalous responses which remain as high priority should be subjected to numerical modeling prior to drill testing to determine the dip, depth and probable geometry of the source.

Respectfully submitted,

Gord Smith,
Aeroquest Limited
April, 2008

Reviewed by:

Doug Garrie,
Aeroquest Limited
April, 2008

APPENDIX 1: SURVEY BOUNDARIES

The following table presents the Shipley block boundaries. All geophysical data presented in this report have been windowed to 100m outside these outlines. X and Y positions are in NAD83 UTM Zone 17N.

X	Y
373800.0	5264800.0
373800.0	5267800.0
376600.5	5267801.6
376600.0	5270200.0
379800.3	5270201.7
379800.0	5272250.0
380799.3	5272251.6
380800.0	5272750.0
381800.1	5272750.1
381800.0	5273050.0
382398.2	5273049.1
382400.0	5273750.0
384400.0	5273750.0
384399.9	5270751.2
384600.0	5270750.0
384599.7	5270251.6
385400.0	5270250.0
385399.0	5269948.8
385600.0	5269950.0
385595.7	5269748.9
385800.0	5269750.0
385799.5	5269544.2
386200.0	5269550.0
386198.3	5269049.6
386600.0	5269050.0
386600.0	5263550.0
386000.0	5263550.0
385998.5	5263751.2
385800.0	5263750.0
385798.6	5263951.0
385600.0	5263950.0
385598.8	5264250.7
384800.0	5264250.0
384798.7	5264747.3
384400.0	5264750.0
384399.9	5265225.8
384200.1	5265224.8
384200.1	5265746.3
383800.0	5265750.0
383801.8	5266745.0
383200.0	5266750.0
383199.7	5267753.8
382194.8	5267749.8
382200.0	5267050.0
381600.7	5267052.0
381600.0	5266750.0
379601.0	5266748.5
379600.0	5264700.0
376600.0	5264700.0
376600.5	5264795.1

APPENDIX 2: MINING CLAIMS

From Ontario Ministry of Northern Development and Mines (April 2008)

Claim Number	Township Area	Recorded Holder	Due Date
3011631	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2011-JUL-19
4213790	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213807	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4207948	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-MAY-03
4213788	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213787	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
3005799	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-OCT-23
3011630	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2011-JUL-19
4213791	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213789	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213782	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213811	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213810	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4207947	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-MAY-03
3005860	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-OCT-23
4213783	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213786	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
1167123	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2009-FEB-18
1167124	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2009-FEB-18
4211849	SHIPLEY (G-1212)	ELLIOTT, MARTIN MILO (100.00 %)	2008-AUG-30
3005789	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-SEP-25
4213804	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213792	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213808	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213809	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213777	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213780	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213776	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213775	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213774	SHIPLEY (G-1212)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213781	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213805	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
1167125	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2009-FEB-18
1167126	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2009-FEB-18
4213806	HONG KONG (G-1144)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04
4213793	FAWN (M-0804)	WALLBRIDGE MINING COMPANY LIMITED (100.00 %)	2008-DEC-04

APPENDIX 3: AEROTEM ANOMALY LISTING

Line	Anom	ID	Cond (s)	Tau	utctime	Bird Height	Easting	Northing
10050	A	K	5.5	234.56	17:59:52	37.48	374210.33	5265948.58
10070	A	N	9.84	313.62	18:02:26	39.2	374400.17	5266022.9
10070	B	K	39.22	626.28	18:02:29	41.59	374406.71	5266093.13
10090	A	N	17.41	417.23	18:05:18	30.7	374590.58	5266686.48
10090	B	K	20.31	450.62	18:05:22	37.01	374591.72	5266588.8
10110	A	N	9.04	300.75	18:08:14	37.77	374796.62	5265967.48
10110	B	K	33.76	581.02	18:08:18	30.13	374798.85	5266048.85
10110	C	N	7.46	273.17	18:08:27	34.84	374806.02	5266203.76
10110	D	K	6.99	264.44	18:08:31	43.25	374801.42	5266297.8
10110	E	K	14.92	386.27	18:08:46	40.73	374799.32	5266594.6
10110	F	N	28.84	537.05	18:08:49	43.37	374793	5266662.35
10110	G	K	79.58	892.1	18:08:57	42.39	374798.92	5266843.17
10130	A	K	125.09	1118.43	18:11:08	45.59	374997.84	5266839.88
10130	B	K	53.93	734.37	18:11:15	35.53	374998.99	5266675.55
10130	C	K	25.47	504.68	18:11:31	57.63	374997.28	5266267.4
10130	D	N	22.25	471.72	18:11:35	53.38	374992.17	5266180.1
10130	E	K	87.87	937.37	18:11:41	42.08	374993.2	5266026.13
10130	F	N	12.29	350.55	18:11:45	55.49	374993.43	5265931.93
10150	A	N	4.2	205.01	18:14:09	39.88	375204.84	5265951.78
10150	B	K	121.76	1103.46	18:14:14	34.38	375198.43	5266071.99
10150	C	N	10.15	318.51	18:14:19	36.3	375199.09	5266180.25
10150	D	K	6.18	248.58	18:14:22	42.21	375204.23	5266259.8
10150	E	K	13.32	364.95	18:14:35	44.69	375207.41	5266599.92
10170	A	K	11.28	335.92	18:16:43	30.43	375389.3	5267349.38
10170	B	K	7.24	269.07	18:16:46	32.38	375394.61	5267284.38
10170	C	N	3.21	179.27	18:17:35	34.74	375397.26	5266099.25
10170	D	K	29.53	543.41	18:17:43	42.37	375392.88	5265898.96
10170	E	N	9.01	300.22	18:17:46	36.19	375388.2	5265824.92
10190	A	K	34.26	585.28	18:20:02	35.69	375588.89	5265944.52
10190	B	N	3.14	177.14	18:20:08	44.04	375589.84	5266084.77
10210	A	K	71.8	847.33	18:22:22	27.88	375805.13	5267532.39
10210	B	N	48.77	698.38	18:22:24	27.24	375804.84	5267501.81
10210	C	K	104.28	1021.2	18:22:27	28.71	375798.21	5267423.35
10210	D	K	87.49	935.37	18:23:22	38.97	375797.46	5265988.79
10230	A	K	62.76	792.23	18:25:40	33.71	376011.14	5265979.14
10230	B	K	66.78	817.18	18:26:10	39.34	376003.32	5266697.19
10230	C	K	57.22	756.41	18:26:48	32.32	376002.03	5267532.77
10230	D	N	11.22	334.98	18:26:51	32.2	375999.13	5267606.09
10250	A	K	169.33	1301.28	18:27:58	38.62	376200.98	5267667.86
10250	B	K	19.39	440.33	18:29:05	30.95	376198.01	5265929.7
10250	C	N	17.43	417.47	18:29:08	31.44	376203.25	5265850.65
10250	D	K	14.66	382.89	18:29:09	33.09	376205.63	5265813.54
20040	A	K	3.29	181.51	20:03:47	32.67	374499.18	5265984.99
20040	B	N	3.87	196.74	20:03:48	36.59	374500.25	5266018.64
20040	C	K	6.63	257.39	20:03:51	43.19	374499.69	5266086.4



Line	Anom	ID	Cond (s)	Tau	utctime	Bird Height	Easting	Northing
20050	A	N	26.77	517.41	20:00:42	41.76	374699.13	5266831.75
20050	B	K	59.92	774.06	20:00:46	42.49	374698.94	5266757.69
20050	C	N	60.6	778.45	20:00:52	47.35	374691.31	5266640.08
20050	D	K	30.18	549.34	20:00:54	45.34	374689.96	5266585.1
20050	E	K	4.96	222.74	20:01:07	50.87	374693.84	5266301.74
20060	A	N	14.11	375.63	19:57:48	56.2	374902.23	5265974.22
20060	B	K	79.45	891.38	19:57:53	49.89	374906.59	5266052.93
20060	C	N	19.96	446.73	19:58:00	46.06	374906.69	5266192.55
20060	D	K	19.11	437.09	19:58:04	46.11	374901.08	5266281.47
20060	E	K	29.13	539.69	19:58:19	39.52	374890.37	5266590.6
20060	F	K	150.4	1226.38	19:58:31	41.93	374899.22	5266857.68
20070	A	K	20.04	447.62	19:54:40	51.21	375095.82	5266994.5
20070	B	N	16.52	406.4	19:54:42	49.55	375101.25	5266926.3
20070	C	K	47.95	692.43	19:54:47	47.23	375104.91	5266809.91
20070	D	K	24.93	499.26	19:54:56	41.54	375098.41	5266575.06
20070	E	N	13.62	369.1	19:55:01	54.17	375107	5266454.9
20070	F	K	47.54	689.49	19:55:08	58.08	375097.24	5266254.12
20070	G	N	43.52	659.7	19:55:12	53.87	375100.74	5266178.28
20070	H	N	34.67	588.83	19:55:22	56.3	375101.25	5265934.96
20080	A	N	9.14	302.35	19:52:03	37.95	375297.48	5266147.11
20080	B	K	18.95	435.26	19:52:06	39.46	375293.98	5266214.84
20080	C	K	124.83	1117.3	19:52:52	34.19	375299.96	5267227.39
20090	A	K	30.84	555.32	19:48:03	56.62	375487.51	5267744.59
20090	B	K	28.8	536.68	19:49:29	49	375489.36	5265873.18
20090	C	N	11.65	341.29	19:49:33	44.2	375483.82	5265794.53
20100	A	N	7.31	270.39	19:45:55	55.65	375693.18	5266058.01
20100	B	K	14.89	385.83	19:46:00	54.43	375695.33	5266151.47
20100	C	K	28.08	529.86	19:46:54	37.63	375704.33	5267391.2
20100	D	N	9.21	303.44	19:46:57	40.1	375703.85	5267464.61
20110	A	N	20.14	448.75	19:42:18	34	375906.17	5267562.81
20110	B	K	63.25	795.31	19:42:22	32.68	375911.01	5267492.62
20110	C	K	186.33	1365.03	19:43:31	39.81	375904.16	5265931.99
20110	D	N	23.67	486.53	19:43:34	41.14	375899.66	5265845.77
20120	A	K	31.12	557.87	19:39:49	46.66	376105.9	5265927.97
20120	B	N	6.6	256.91	19:41:01	42.96	376095.4	5267609.85
20120	C	N	6.51	255.07	19:41:06	45.67	376099.49	5267733.64
20180	A	N	0.78	88.02	19:16:57	47.09	377300.47	5269304.59
20190	A	K	11.68	341.81	19:10:11	49.5	377511.84	5268634.18
20190	B	K	10.72	327.38	19:10:24	43.46	377500.87	5268338.07
20190	C	K	24.51	495.07	19:10:50	45.33	377507.18	5267731.56
20190	D	N	2.64	162.41	19:10:58	62.51	377492.69	5267529.59
20190	E	K	9.9	314.67	19:11:01	62.14	377496.91	5267441.18
20200	A	K	51.11	714.89	19:06:25	46.12	377698.46	5267575.84
20200	B	K	118.33	1087.81	19:06:31	34.47	377701.46	5267719.36
20200	C	K	6.01	245.16	19:07:16	46.74	377696.57	5268767.41
20210	A	K	168.29	1297.29	19:01:31	47.39	377907.06	5267662.45
20250	A	N	1.43	119.61	17:42:13	36.33	378697.44	5264928.42



Line	Anom	ID	Cond (s)	Tau	utctime	Bird Height	Easting	Northing
20440	A	N	1.58	125.8	15:15:43	38.04	382498.51	5273757.63
20450	A	N	*	*	15:06:59	44.14	382702.15	5273788.49
20480	A	N	0.31	55.63	21:17:25	46.52	383291.93	5269444.27
20500	A	N	*	*	21:06:12	37.44	383700.77	5269263.72
20500	B	K	79.23	890.11	21:08:47	31.51	383684.92	5273166.02
20510	A	N	42.58	652.53	19:53:59	30.05	383922.15	5273315.93
20510	B	K	72.26	850.04	19:54:02	26.89	383918.14	5273242.23
20520	A	N	18.28	427.52	19:52:36	41.49	384109.8	5273378.7
20530	A	N	8.25	287.19	19:40:56	30.88	384307.84	5273390.67
20550	A	K	9.67	310.94	19:32:49	39.82	384704.83	5266185.67
19030	A	K	34.14	584.26	17:48:19	47.57	375983.63	5266656.69
19030	B	N	35.1	592.44	17:48:57	40.83	375076.33	5266662.86
19030	C	K	75.68	869.94	17:49:03	28.43	374975.08	5266660.75
19030	D	K	131.25	1145.63	17:49:19	37.31	374684.43	5266672.9
29010	A	N	0.39	62.77	18:42:45	29.47	382301.25	5273654.36
29041	A	K	138.73	1177.82	19:08:10	28.1	377807.01	5267659.76
29041	B	K	135	1161.88	19:09:23	36.45	376136.4	5267662.91
29041	C	N	14.4	379.41	19:09:27	28.18	376036.11	5267657.51

APPENDIX 4: DESCRIPTION OF DATABASE FIELDS

The GDB file is a Geosoft binary database. In the database, the Survey lines and Tie Lines are prefixed with an "L" for "Line" and "T" for "Tie".


COLUMN	UNITS	DESCRIPTOR
Line		Line number
Flight		Flight #
emfid		AERODAS Fiducial
utctime	hh:mm:ss.ss	UTC time
X	m	UTM Easting (NAD83, Zone 17N)
Y	m	UTM Northing (NAD83, Zone 17N)
Galtf	m	GPS altitude of Mag bird
ralt	m	Radar Altimeter based on helicopter height above terrain
bheight	m	Terrain clearance of EM bird
dtm	m	Digital Terrain Model
Basemagf	nT	Base station total magnetic intensity
magF	nT	Final levelled total magnetic intensity
Zon	nT/s	Processed Streaming On-Time Z component Channels 1-16
Zoff	nT/s	Processed Streaming Off-Time Z component Channels 0-16
Xon	nT/s	Processed Streaming On-Time X component Channels 1-16
Xoff	nT/s	Processed Streaming Off-Time X component Channels 0-16
pwrline		powerline monitor data channel
Grade		Classification from 1-7 based on conductance of conductor pick
Anom_labels		Alphanumeric label of conductor pick
Off_Con	S	Off-time conductance at conductor pick
Off_Tau	µs	Off-time decay constant at conductor pick
Anom_ID		Anomaly Character (K= thick, N = thin)
Off_allcon	S	Off-time conductance
Off_AllTau	µs	Off-time decay constant
TranOff		Transmission Off
TranOn		Transmission On
TranPeak		Transmission Peak
TranSwitch		Transmission Switch

APPENDIX 5: AEROTEM DESIGN CONSIDERATIONS

Helicopter-borne EM systems offer an advantage that cannot be matched from a fixed-wing platform. The ability to fly at slower speed and collect data with high spatial resolution, and with great accuracy, means the helicopter EM systems provide more detail than any other EM configuration, airborne or ground-based. Spatial resolution is especially important in areas of complex geology and in the search for discrete conductors. With the advent of helicopter-borne high-moment time domain EM systems the fixed wing platforms are losing their *only* advantage – depth penetration.

Advantage 1 – Spatial Resolution

The AeroTEM system is specifically designed to have a small footprint. This is accomplished through the use of concentric transmitter-receiver coils and a relatively small diameter transmitter coil (5 m). The result is a highly focused exploration footprint, which allows for more accurate “mapping” of discrete conductors. Consider the transmitter primary field images shown in Figure 1, for AeroTEM versus a fixed-wing transmitter.



The footprint of AeroTEM at the earth's surface is roughly 50m on either side of transmitter

The footprint of a fixed-wing system is roughly 150 m on either side of the transmitter

Figure 1. A comparison of the footprint between AeroTEM and a fixed-wing system, highlights the greater resolution that is achievable with a transmitter located closer to the earth's surface. The AeroTEM footprint is one third that of a fixed-wing system and is symmetric, while the fixed-wing system has even lower spatial resolution along the flight line because of the separated transmitter and receiver configuration.

At first glance one may want to believe that a transmitter footprint that is distributed more evenly over a larger area is of benefit in mineral exploration. In fact, the opposite is true; by energizing a larger surface area, the ability to energize and detect discrete conductors is reduced. Consider, for example, a comparison between AeroTEM and a fixed-wing system over the Mesamax Deposit (1,450,000 tonnes of 2.1% Ni, 2.7% Cu, 5.2 g/t Pt/Pd). In a test survey over three flight lines spaced 100 m apart, AeroTEM detected the Deposit on all three flight lines. The fixed-wing system detected the Deposit only on two flight lines. In exploration programs that seek to expand the flight line spacing in an effort to reduce the cost of the airborne survey, discrete conductors such as the Mesamax Deposit can go undetected. The argument often put forward in favour of using fixed-wing systems is that because of their larger footprint, the flight line spacing can indeed be widened. Many fixed-wing surveys are flown at 200 m or 400 m. Much of the survey work performed by Aeroquest has been to survey in areas that were previously flown at these wider line spacings. One of the reasons for AeroTEM's impressive discovery record has been the strategy of flying closely spaced lines and finding all the discrete near-surface conductors. These higher resolution surveys are being flown within existing mining camps, areas that improve the chances of discovery.




Figure 2. Fixed-wing (upper) and AeroTEM (lower) comparison over the eastern limit of the Mesamax Deposit, a Ni-Cu-PGE zone located in the Raglan nickel belt and owned by Canadian Royalties. Both systems detected the Deposit further to the west where it is closer to surface.

The small footprint of AeroTEM combined with the high signal to noise ratio (S/N) makes the system more

suitable to surveying in areas where local infrastructure produces electromagnetic noise, such as power lines and railways. In 2002 Aeroquest flew four exploration properties in the Sudbury Basin that were under option by FNX Mining Company Inc. from Inco Limited. One such property, the Victoria Property, contained three major power line corridors.

The resulting AeroTEM survey identified all the known zones of Ni-Cu-PGE mineralization, and detected a response between two of the major power line corridors but in an area of favorable geology. Three boreholes were drilled to test the anomaly, and all three intersected sulphide. The third borehole encountered 1.3% Ni, 6.7% Cu, and 13.3 g/t TPMs over 42.3 ft. The mineralization was subsequently named the Powerline Deposit.

The success of AeroTEM in Sudbury highlights the advantage of having a system with a small footprint, but also one with a high S/N. This latter advantage is achieved through a combination of a high-moment (high signal) transmitter and a rigid geometry (low noise). Figure 3 shows the Powerline Deposit response and the response from the power line corridor at full scale. The width of power line response is less than 75 m.




Figure 3. The Powerline Deposit is located between two major power line corridors, which make EM surveying problematic. Despite the strong response from the power line, the anomaly from the Deposit is clearly detected. Note the thin formational conductor located to the south. The only way to distinguish this response from that of two closely spaced conductors is by interpreting the X-axis coil response.

Advantage 2 – Conductance Discrimination

The AeroTEM system features full waveform recording and as such is able to measure the on-time response due to high conductance targets. Due to the processing method (primary field removal), there is attenuation of the response with increasing conductance, but the AeroTEM on-time measurement is still superior to systems that rely on lower base frequencies to detect high conductance targets, but do not measure in the on-time.


The peak response of a conductive target to an EM system is a function of the target conductance and the EM system base frequency. For time domain EM systems that measure only in the off-time, there is a drop in the peak response of a target as the base frequency is lowered for all conductance values below the peak system

response. For example, the AeroTEM peak response occurs for a 10 S conductor in the early off-time and 100 S in the late off-time for a 150 Hz base frequency. Because base frequency and conductance form a linear relationship when considering the peak response of any EM system, a drop in base frequency of 50% will double the conductance at which an EM system shows its peak response. If the base frequency were lowered from 150 Hz to 30 Hz there would be a fivefold increase in conductance at which the peak response of an EM occurred.


However, in the search for highly conductive targets, such as pyrrhotite-related Ni-Cu-PGM deposits, a fivefold increase in conductance range is a high price to pay because the signal level to lower conductance targets is reduced by the same factor of five. For this reason, EM systems that operate with low base frequencies are not suitable for general exploration unless the target conductance is more than 100 S, or the target is covered by conductive overburden.

Despite the excellent progress that has been made in modeling software over the past two decades, there has been little work done on determining the optimum form of an EM system for mineral exploration. For example, the optimum configuration in terms of geometry, base frequency and so remain unknown. Many geophysicists would argue that there is no single ideal configuration, and that each system has its advantages and disadvantages. We disagree.

When it comes to detecting and discriminating high-conductance targets, it is necessary to measure the pure in phase response of the target conductor. This measurement requires that the measured primary field from the transmitter be subtracted from the total measured response such that the secondary field from the target conductor can be determined. Because this secondary field is in-phase with the transmitter primary field, it must be made while the transmitter is turned on and the transmitter current is changing. The transmitted primary field is several orders of magnitude larger than the secondary field. AeroTEM uses a bucking coil to reduce the primary field at the receiver coils. The only practical way of removing the primary field is to maintain a rigid geometry between the transmitter, bucking and receiver coils. This is the main design consideration of the AeroTEM airframe and it is the only time domain airborne system to have this configuration.



The off-time AeroTEM response for the 16 channel configuration.



The on-time response assuming 100% removal of the measured primary field.

Figure 4. The off-time and on-time response nomogram of AeroTEM for a base frequency of 150 Hz. The on-time response is much stronger for higher conductance targets and this is why on-time measurements are more important than lower frequencies when considering high conductance targets in a resistive environment.

Advantage 3 – Multiple Receiver Coils

AeroTEM employs two receiver coil orientations. The Z-axis coil is oriented parallel to the transmitter coil and both are horizontal to the ground. This is known as a maximum coupled configuration and is optimal for detection. The X-axis coil is oriented at right angles to the transmitter coil and is oriented along the line-of-flight.

This is known as a minimum coupled configuration, and provides information on conductor orientation and thickness. These two coil configurations combined provide important information on the position, orientation, depth, and thickness of a conductor that cannot be matched by the traditional geometries of the HEM or fixed-wing systems. The responses are free from a system geometric effect and can be easily compared to model type curves in most cases. In other words, AeroTEM data is very easy to interpret. Consider, for example, the following modeled profile:




Figure 5. Measured (lower) and modeled (upper) AeroTEM responses are compared for a thin steeply dipping conductor. The response is characterized by two peaks in the Z-axis coil, and a cross-over in the X-axis coil that is centered between the two Z-axis peaks. The conductor dips toward the higher amplitude Z-axis peak. Using the X-axis cross-over is the only way of differentiating the Z-axis response from being two closely spaced conductors.

HEM versus AeroTEM

Traditional helicopter EM systems operate in the frequency domain and benefit from the fact that they use narrowband as opposed to wide-band transmitters. Thus all of the energy from the transmitter is concentrated in

a few discrete frequencies. This allows the systems to achieve excellent depth penetration (up to 100 m) from a transmitter of modest power. The Aeroquest Impulse system is one implementation of this technology.

The AeroTEM system uses a wide-band transmitter and delivers more power over a wide frequency range. This frequency range is then captured into 16 time channels, the early channels containing the high frequency information and the late time channels containing the low frequency information down to the system base frequency. Because frequency domain HEM systems employ two coil configurations (coplanar and coaxial) there are only a maximum of three comparable frequencies per configuration, compared to 16 AeroTEM off-time and 12 AeroTEM on-time channels.

Figure 6 shows a comparison between the Dighem HEM system (900 Hz and 7200 Hz coplanar) and AeroTEM (Z-axis) from surveys flown in Raglan, in search of highly conductive Ni-Cu-PGM sulphide. In general, the AeroTEM peaks are sharper and better defined, in part due to the greater S/N ratio of the AeroTEM system over HEM, and also due to the modestly filtered AeroTEM data compared to HEM. The base levels are also better defined in the AeroTEM data. AeroTEM filtering is limited to spike removal and a 5-point smoothing filter. Clients are also given copies of the raw, unfiltered data.




Figure 6. Comparison between Dighem HEM (upper) and AeroTEM (lower) surveys flown in the Raglan area. The AeroTEM responses appear to be more discrete, suggesting that the data is not as heavily filtered as the HEM data. The S/N advantage of AeroTEM over HEM is about 5:1.

Aeroquest Limited is grateful to the following companies for permission to publish some of the data from their respective surveys: Wolfden Resources, FNX Mining Company Inc, Canadian Royalties, Nova West Resources, Aurogin Resources, Spectrem Air. Permission does not imply an endorsement of the AeroTEM system by these companies.

APPENDIX 6: AEROTEM INSTRUMENTATION SPECIFICATION SHEET

AEROTEM Helicopter Electromagnetic System

System Characteristics

- Transmitter: Triangular Pulse Shape Base Frequency 90 Hz
- Tx On Time – 1,833 (90 Hz) μ s
- Tx Off Time – 3,667 (90 Hz) μ s
- Loop Diameter - 10 m
- Peak Current - 455 A
- Peak Moment – 183,131 NIA
- Typical Z Axis Noise at Survey Speed = 5 nT/s peak to peak
- Sling Weight: 1000 lb
- Length of Tow Cable: 53 m
- Bird Survey Height: 30 m nominal

Receiver




- Two Axis Receiver Coils (x, z) positioned at centre of transmitter loop
- Selectable Time Delay to start of first channel 21.3 , 42.7, or 64.0 ms

Display & Acquisition

- AERODAS Digital recording at 120 samples per decay curve at a maximum of 300 curves per second (27.778 μ s channel width)
- RMS Channel Widths: 52.9, 132.3, 158.7, 158.7, 317.5, 634.9 μ s
- Recording & Display Rate = 10 readings per second.
- On-board display - six channels Z-component and 1 X-component

System Considerations

Comparing a fixed-wing time domain transmitter with a typical moment of 500,000 NIA flying at an altitude of 120 m with a Helicopter TDEM at 30 m, notwithstanding the substantial moment loss in the airframe of the fixed wing, the same penetration by the lower flying helicopter system would only require a sixty-fourth of the moment. Clearly the AeroTEM system with nearly 183.131 NIA has more than sufficient moment. The airframe of the fixed wing presents a response to the towed bird, which requires dynamic compensation. This problem is non-existent for AeroTEM since transmitter and receiver positions are fixed. The AeroTEM system is completely portable, and can be assembled at the survey site within half a day.



SURVEY SPECIFICATIONS:
 Survey flown: Jan. 31 - Feb. 06, 2008
 Traverse line spacing: 100 & 200 metres
 Traverse line direction: N-S (0° azimuth)
 Nominal EM bird height: 30 metres
 Aircraft: Aerospatiale A-Star 350BA (C-GJIX)


INSTRUMENTATION:
 Data acquisition: ADAS & RMS DGR-33
 Magnetometer: Geometrics G-823A cesium vapour
 Installation: Towed bird 33 m above EM bird
 Sensitivity: .001 nanoTesla
 Electromagnetics: AeroTEM III System (NOVEMBER)
 Configuration: Towed bird

NAVIGATION:
 Navigation: Differential Global Positioning System (DGPS)
 Navigation equipment: AGNAV with MID-TECH RX400p receiver
 Radar Altimeter: Terra TRA3000/TRI-30

DATA PROCESSING:
 Magnetics: diurnal, tideline and micro-leveling corrections

POSITIONING:
 Datum: NAD83
 Major Axis: 6378137.000
 Eccentricity: 0.081819191

MAP PROJECTION:
 Projection: Universal Transverse Mercator
 Central Meridian: 81°W (Zone 17)
 Central Scale Factor: 0.9996
 False Easting/Northing: 500,000m/0m




Wallbridge Mining Company Ltd.
 Gogama area, Northern Ontario

AEROTEM Z0 OFF-TIME

Shipley Block
 NTS 041010

AEROQUEST
 7687 Bath Road, Mississauga, ON, CANADA L4T 3T1
 Tel: (905) 672-9129 Fax: (905) 672-7083
 www.aeroquest.ca

April 2008



The topographic data base was derived from 1:50000 NRC (Natural Resources Canada) NTDB data
 Background shading derived from NASA SRTM data
 Inset data derived from Natural Resources Canada Atlas of Canada Base Maps

This map accompanies the technical report entitled "Report on a Helicopter-Borne Magnetic and Electromagnetic Survey, Shipley Block, Gogama area, Northern Ontario, by Aeroquest Limited, April 2008"

Grid North
 NAD83-Zone17



Legend

- Rail
- Trails
- Roads
- Mining Area
- Mining Claims
- Wetland
- Lake

TMI Contour Interval

- 10nT
- 500nT
- 5000nT

Off-Time Anomaly Symbols

- >50S
- 35-50S
- 20-35S
- 10-20S
- 5-10S
- 1-5S
- <1S

anomaly label $\frac{K}{A}$ $\frac{125}{36}$ **decay constant (µs)**
thick/thin source **off-time conductance (S)**

TMI nT

SURVEY SPECIFICATIONS:
 Survey flown: Jan. 31 - Feb. 06, 2008
 Traverse line spacing: 100 & 200 metres
 Traverse line direction: N-S (0° azimuth)
 Nominal EM bird height: 30 metres
 Aircraft: Aerospatiale A-Star 350BA (C-GJIX)


INSTRUMENTATION:
 Data acquisition: ADAS & RMS DGR-33
 Magnetometer: Geometrics G-823A cesium vapour
 Installation: Towed bird 33 m above EM bird
 Sensitivity: .001 nanoTesla
 Electromagnetics: AeroTEM III System (NOVEMBER)
 Configuration: Towed bird

NAVIGATION:
 Navigation: differential Global Positioning System (DGPS)
 Navigation equipment: AGNAV with MID-TECH RX400p receiver
 Radar Altimeter: Terra TRA3000/TRI-30

DATA PROCESSING:
 Magnetics: diurnal, tideline and micro-leveling corrections

POSITIONING
 Datum: NAD83
 Major Axis: 6378137.000
 Eccentricity: 0.081819191

MAP PROJECTION
 Projection: Universal Transverse Mercator
 Central Meridian: 81°W (Zone 17)
 Central Scale Factor: 0.9996
 False Easting/Northing: 500,000m/0m



Wallbridge Mining Company Ltd.
 Gogama area, Northern Ontario





TOTAL MAGNETIC INTENSITY

Shipley Block
 NTS 041010



The topographic data base was derived from 1:50000 NRC (Natural Resources Canada) NTDB data
 Background shading derived from NASA SRTM data
 Inset data derived from Natural Resources Canada 'Atlas of Canada Base Map'

This map accompanies the technical report entitled 'Report on a Helicopter-Borne Magnetic and Electromagnetic Survey, Shipley Block, Gogama area, Northern Ontario, by Aeroquest Limited, April 2008'



SURVEY SPECIFICATIONS:
 Survey flown: Jan. 31 - Feb. 06, 2008
 Traverse line spacing: 100 & 200 metres
 Traverse line direction: N-S (0° azimuth)
 Nominal EM bird height: 30 metres
 Aircraft: Aerospatiale A-Star 350BA (C-GJIX)


INSTRUMENTATION:
 Data Acquisition: ADAS & RMS DGR-33
 Magnetometer: Geometrics G-823A cesium vapour
 Installation: Towed bird 33 m above EM bird
 Sensitivity: .001 nanoTesla
 Electromagnetics: AerOTEM III System (NOVEMBER)
 Configuration: Towed bird

NAVIGATION:
 Navigation: Differential Global Positioning System (DGPS)
 Navigation equipment: AGNAV with MID-TECH RX400p receiver
 Radar Altimeter: Terra TRA3000/TRI-30

DATA PROCESSING:
 Magnetics: diurnal, tideline and micro-leveling corrections

POSITIONING:
 Datum: NAD83
 Major Axis: 6378137.000
 Eccentricity: 0.081819191

MAP PROJECTION:
 Projection: Universal Transverse Mercator
 Central Meridian: 81°W (Zone 17)
 Central Scale Factor: 0.9995
 False Easting/Northing: 500,000m/0m



Wallbridge Mining Company Ltd.
 Gogama area, Northern Ontario

AEROTEM OFF-TIME PROFILES

Shipley Block

NTS 041010

7687 Bath Road, Mississauga, ON, CANADA L4T 1T1
 Tel: (905) 672-9129 Fax: (905) 672-7083
 www.aeroquest.ca

April 2008

