GEOPHYSICAL REPORT

For

GOLDEN CHALICE RESOURCES INC.

ON THE

FOLLOW-UP IP SURVEYS PENHORWWOD PROPERTY

PENHORWOOD TOWNSHIP PORCUPINE MINING DIVISION NORTHEASTERN, ONTARIO

Prepared by: J.C.Grant, CET,
May 2010

JULY 0 4 2010

GEOSCIENCE ASSESSMENT
OFFICE

TABLE OF CONTENTS

		PAGE
INTRODUCTION:		1
PROPERTY LOCATION	ON AND ACCESS:	1
CLAIM BLOCK		2
PERSONNEL		2
GROUND PROGRAM		2,3
PROPERTY GEOLOG	Y	3
MAGNETIC AN VLF-	EM SURVEY RESULTS, 2010	4
IP SURVEY RESULTS	S	4,5
CONCLUSIONS AND	RECOMMENDATIONS	6
CERTIFICATE		
LIST OF FIGURES:	1.) LOCATION MAP 2.) PROPERTY LOCATION MAP 3.) CLAIM MAP 4.) GEOLOGY MAP	
APPENDICES:	A.) INSTRUMENTATION G.D.D. IP RECEIVER AND 3.6 TRANSMITTER	KWATT
POCKET MAPS:	INDIVIDUAL LINE PSEUDO-SECTIONS OF IP SURVEY 0+00 TO LINE 2700ME, NOT INCLUDING LINES 400ME 2500ME, SCALE 1:2500 MAGNETIC, VLF-EM AND IP COMPILATION MAP, 1:50	AND

INTRODUCTION:

The services of Exsics Exploration Limited were retained by Mr. K. Montgomery, on behalf of the Company, Golden Chalice Resources Inc., to complete a follow-up Induced Polarization, (IP), program on the Penhorwood Property, which is located in the northeast portion of Penhorwood Township of the Porcupine Mining Division of Northeastern Ontario.

The purpose of this present program was to follow up on an initial ground program completed in the fall of 2009 that was completed across a portion of the grid that had returned elevated gold values from a soil sampling program. This recent program consisted of expanding the original grid to the east and west to define and outline favorable horizons that would lend themselves to the possibility of larger and more economical gold deposits.

The present IP ground program commenced in the middle of February and was completed by the end of March 2010. This IP program was done to follow-up on the total field magnetic survey that was completed in conjunction with a VLF-EM survey that had been done across the entire cut grid. Initially a Time Domain IP survey using the pole-dipole array was completed in the latter part of 2009 and it covered lines 700ME to 1300ME.


In all, a total of 26.5 kilometers of new cutting was added to the existing 8.5 kilometers for a total of 34.0 kilometers of grid lines that were cut across the property. The new cutting of 26.5 kilometers has now been covered by the IP surveys and those results will be incorporated into the original survey results in this report.

PROPERTY LOCATION AND ACCESS:

The Penhorwood property is situated in the northeast section of the Township, which is part of the Porcupine Mining Division. More specifically, the property is situated approximately 2.1 kilometers to the northeast of Steepe Lake that is the southern most lake of a chain of lakes that lie to the immediate southwest of the grid area. The main Kenogaming limber road cuts across the grid area in a northeast to southwest direction. Refer to Figures 1 and 2. The entire property is located approximately 60 kilometers southwest of the City of Timmins.

Access to the grid during the survey period was ideal. Highway 101 travels west from Timmins and crosses the north end of a good logging road locally called the Kenogaming lumber road. This gravel road travels south and southwest through Penhorwood and crosses the northern section of the grid area.





CLAIM BLOCK:

The claim numbers that represent the portion of the property that was covered by this current ground program are as follows.

4207034,	16 units
4207036,	16 units
4207037,	10 units
4207042,	16 units
4207043,	16 units
4207044	16 units

Refer to Figure 3 of this report that was copied from MNDM Plan Map G-3244 of Penhorwood Township for the positioning of the claims within the Township.

PERSONNEL:

The field crew directly responsible for the collection of all of the raw IP field data were as follows.

J. Hamlin	Timmins, Ontario,
D. Poirier	Timmins, Ontario,
D. Collins	Timmins, Ontario
S. Chartrand	Timmins, Ontario
J. Harrell	Timmins, Ontario

The entire program was completed under the direct supervision of J.C.Grant and all of the plotting, compilation, interpretation and reports were completed by in-house staff.


GROUND PROGRAM:

The ground program was completed in two stages. The first stage was to extend the original to the east and west. This was done by extending the original base line from 1300ME to 2700ME and from 700ME to line 0+00. A tie line labeled 500MN was cut parallel to the base line at it extended from 2700ME to 0+00. Lines 2700ME to 1900ME were cut from tie line 250MS to 500MN. Lines 1800ME to 1400ME were cut from 250MS to 1000MN. Lines 1300ME and 1200ME were cut from 500MS to 1000MN. Lines 1100ME to 700ME were cut from 500MS to 750MN and lines 600ME to line 0 were cut from 500MS to 500MN. The base line was cut and chained with 25 meter station intervals from line 0+00ME to and including 2700ME. All of the cross lines were also chained with 25 meter station intervals that have been metal tagged.

Once the line cutting was completed, Exsics then commenced an IP survey that was done across all of the new cut lines.

PENHORWOOD	4207035	2005-Jun-07	2010-Jun-07	A	100 %	\$ 400	\$ 1,200	1 1	\$ 0
PENHORWOOD	4207034		2010-Jun-07	A		\$ 6,400	\$ 19,200	\$ 3,438	\$0
PENHORWOOD	4207033	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200		\$0
PENHORWOOD	4207032		2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$0	\$0
PENHORWOOD	4207030		2010-Jun-07	A	100 %	\$ 4,800	\$ 14,400	\$0	\$0
PENHORWOOD	4201493		2010-Mar-23	A	100 %	\$ 3,200	\$ 6,400	\$0	\$0
PENHORWOOD	4201492		2010-Mar-23	A	100 %	\$ 6,400	\$ 12,800	\$ 0 \$ 0	\$ 0 \$ 0
PENHORWOOD	3019491		2009-Nov-19	A	100 %	\$ 1,230	\$ 4,770	\$0	\$ 0
PENHORWOOD	3019490		2010-Dec-18	A	100 %	\$ 6,000	\$ 6,000	\$0	\$ 0
PENHORWOOD	3019488		2010-Dec-18	<u>A</u>	100 %	\$ 6,400	\$ 6,400	\$ 0	\$ 0
PENHORWOOD	3019487		2010-Nov-19	A	100 %	\$ 4,000	\$ 4,000	\$ 0	\$0
PENHORWOOD	3019024		2010-Apr-24	A	100 %	\$ 800	\$ 1,600	\$0	\$ 0
PENHORWOOD	3000605		2011-Jan-02	A	100 %	\$ 400	\$ 2,000	\$0	\$ 0
PENHORWOOD	3000604	2003-Oct-15		A	100 %	\$ 800	\$ 4,000	\$ 0	\$0
PENHORWOOD	3000603			A					
		22	2011-May- 122 2010-Oct-15		100 %	\$ 800	\$ 4,000	\$ 0	\$0
MACKLEM	4223969	2007-Jun-21 2007-May-	2010-Jun-21 2011-May-	A	100 %	\$ 6,000			\$ 0
MACDIARMID MACDIARMID	4223969	2007-Jun-21	2010-Jun-21	A	100 %	\$ 3,600	_ 		\$ 0
MACDIARMID MACDIARMID	4223965	2007-Jun-21 2007-Jun-21	2010-Jun-21	A	100 %	\$ 4,800	\$ 4,800		\$0
MACDIARMID	4223965	2007-Jun-21	2010-Jun-21	A	100 %	\$ 4,400	\$ 4,400		\$ 0
MACDIARMID MACDIARMID	4223963	2007-Jun-21 2007-Jun-21	2010-Jun-21	A	100 %	\$ 6,400	\$ 6,400		$-\frac{30}{$0}$
MACDIARMID MACDIARMID	<u>4223962</u> <u>4223963</u>	2007-Jun-21 2007-Jun-21	2010-Jun-21	A A	100 %	\$ 4,800	\$ 4,800	\$ 0	\$ 0
MACDIARMID MACDIARMID	4223961	2007-Jun-21 2007-Jun-21	2010-Jun-21 2010-Jun-21	A	100 %	\$ 4,000	\$ 4,000		\$0
MACDIARMID MACDIARMID	4223960	2007-Jun-21 2007-Jun-21	2010-Jun-21 2010-Jun-21	A	100 %	\$ 4,800	\$ 3,600	\$ 0	\$ 0
LOVELAND MACDIARMID	4224273	2008-Jan-07 2007-Jun-21	2010-Sep-07 2010-Jun-21	A	100 %	\$ 4,800	\$ 4,800	\$ 0	\$0
LOVELAND	4224272		2010-Sep-07 2010-Sep-07		100 %	\$ 4,000	\$ 0 \$ 0	\$ 0	\$0
		2008-Jan-07 2008-Jan-07	2010-Sep-07 2010-Sep-07	A	100 %	\$ 4,000	\$0	\$0	\$0
LOVELAND	4224270	2008-Jan-07 2008-Jan-07	2010-Sep-07	A	100 %	\$ 2,400	\$ 0	\$ 0	\$0
LOVELAND	4224270	2007-May- 22 2008-Jan-07	2011-May- 22 2010-Sep-07	A	100 %	\$ 4,000	\$ 9,000	\$ 0	\$0
LANGMUIR LANGMUIR	4220197	2007-May- 22 2007-May-	2010-May- 22 2011-May-	A	100 %	\$ 4,800	\$ 9,600	\$ 0	\$ 0 \$ 0
LANGMUIR	4207038	2005-Jul-18	2011-Jul-18	A		\$ 1,000	\$ 1,200		\$0
LANGMUIR	4203571	2005-Feb-08		A	100 %	\$ 6,400 \$ 1,600		\$ 109,054 \$ 54,983	\$0
LANGMUIR	4203570	2005-Feb-08		A					\$0
LANGMUIR	4203569	2005-Feb-08		A	100 %	\$ 3,200 \$ 400	\$ 12,800	\$ 102,723	<u> </u>
LANGMUIR	4203568	2005-Feb-08		A	100 %	\$ 3,200		\$ 0	\$0
LANGMUIR	4203567	2005-Feb-08		A	100 %	\$ 6,400	\$ 25,600 \$ 12,800	\$ 0	<u> </u>
LANGMUIR	4203564	2005-Feb-08		A	100 %	\$ 6,000	\$ 24,000	\$ 0 \$ 0	\$ 0 \$ 0
LANGMUIR	4203563	2005-Feb-08		A	100 %	\$ 4,000	\$ 16,000	\$0	\$ 0
LANGMUIR	4203498	2005-Jul-18	2014-Jul-18	A	100 %	\$ 3,200	\$ 22,400	1,271,081	\$ 0
LANGMUIR	4202816		2011-Jun-06	Α	100 %	\$ 3,200	\$ 12,800	\$ 0	\$ 0
LANGMUIR	4202815	2005-Jun-06	2011-Jun-06	A	100 %	\$ 1,600	\$ 6,400	\$ 0	\$ 0
LANGMUIR	4202814	2005-Jun-06	2011-Jun-06	A	100 %	\$ 400	\$ 1,600	\$ 0	\$ 0
LANGMUIR	4202748	2005-Jul-18	2014-Jul-18	A	100 %	\$ 4,400	\$ 30,800	\$ 3,418	\$ 0
LANGMUIR	4202744		2011-Jun-06	<u>A</u>	100 %	\$ 800	\$ 3,200	\$ 0	\$ 0
LANGMUIR	4201290	2005-Nov-01		A	100 %	\$ 1,600	\$ 4,800	\$ 0	\$ 0
	The state of the s								_
LANGMUIR	4201289	2005-Nov-01	12010-Nov-011	Α	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0

PENHORWOOD	4207036	2005-Jun-07		A	100 %	\$ 6,400	\$ 19,200	\$ 1,526	\$ 0
PENHORWOOD	4207037	2005-Jun-07	2010-Jun-07	A	100 %	\$ 4,000	\$ 12,000	\$ 2,880	\$ 0
PENHORWOOD	4207040	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,000	\$ 18,000	\$ 0	\$ 0
PENHORWOOD	4207041	2005-Jun-07	2010-Jun-07	_A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207042	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207043	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 1,426	\$ 0
PENHORWOOD	4207044	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207046	2005-Jun-07	2009-Nov-25	A	100 %	\$ 2,727	\$ 16,473	\$ 0	\$ 0
PENHORWOOD	4207047	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207048	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207049	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$0
PENHORWOOD	4207050	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207052	2005-Jun-07	2011-Jun-07	A	100 %	\$ 6,400	\$ 25,600	\$ 0	\$ 0
PENHORWOOD	4207053	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207054	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207055	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207056	2005-Jun-07	2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207057	2005-Jun-07	2010-Jun-07	A	100 %	\$ 400	\$ 1,200	\$ 0	\$ 0
PENHORWOOD	4207058		2010-Jun-07	A	100 %	\$ 4,800	\$ 14,400	\$ 0	\$0
PENHORWOOD	4207060	2005-Jun-07	2010-Jun-07	A	100 %	\$ 5,600	\$ 16,800	\$ 0	\$0
PENHORWOOD	4207061		2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207062		2010-Jun-07	A	100 %	\$ 6,400	\$ 19,200	\$ 0	\$ 0
PENHORWOOD	4207914	2005-Jun-07	2010-Jun-07	A	100 %	\$ 3,600	\$ 10,800	\$ 0	\$ 0
PENHORWOOD	4207916	+	2010-Jun-07	A	100 %	\$ 6,000	\$ 18,000	\$ 0	\$ 0
PENHORWOOD	4220806		2010-Apr-30	A	100 %	\$ 1,600	\$ 1,600	\$ 0	\$ 0
PENHORWOOD	4227175		2009-Nov-19	A	100 %	\$ 1,200	\$ 0	\$ 0	\$ 0
PENHORWOOD	4241832	2008-Jul-11	2010-Jul-11	A	100 %	\$ 4,800	\$ 0	\$ 0	\$ 0
SOTHMAN (PORC)	1226833	1998-May- 13	2011-May- 13	A	100 %	\$ 1,333	\$ 27,467	\$ 0	\$ 0
THOMAS	4220191	2007-May- 22	2010-May- 22	A	100 %	\$ 6,400	\$ 6,400	\$ 0	\$ 0
THOMAS	4220192	2007-May- 22	2011-May- 22	A	100 %	\$ 6,400	\$ 12,800	\$ 0	\$ 0
THOMAS	4220193	2007-May- 22	2010-May- 22	Α	100 %	\$ 6,400	\$ 6,400	\$ 0	\$ 0
THOMAS	4220194	2007-May- 22	2010-May- 22	A	100 %	\$ 6,400	\$ 6,400	\$ 0	\$ 0
THOMAS	4220219	2007-May- 22	2011-May- 22	A	100 %	\$ 6,400	\$ 12,800	\$ 0	\$ 0
THOMAS	4220220	2007-May- 22	2011-May- 22	Α	100 %	\$ 6,400	\$ 12,800	\$ 0	\$0
THORBURN	4224268	2008-Jan-07	2010-Sep-07	A	100 %	\$ 4,800	\$ 0	\$ 0	\$ 0
THORBURN	4224269	2008-Jan-07	2010-Sep-07	A	100 %	\$ 3,600	\$ 0	\$ 0	\$0
WHITNEY	4202630	2006-Oct-20	2010-Oct-20	A	100 %	\$ 3,200	\$ 6,400	\$ 0	\$ 0
WHITNEY	4202634	2006-Oct-20	2010-Oct-20	A	100 %	\$ 5,600	\$ 11,200	\$ 0	\$ 0
WHITNEY	4210987	2006-Oct-12	2010-Oct-12	A	100 %	\$ 400	\$ 800	\$ 0	\$ 0
WHITNEY	4211030	2006-Oct-20	2010-Oct-20	A	100 %	\$ 1,600	\$ 3,200	\$ 0	\$ 0
WHITNEY	4211031	2006-Oct-20	2010-Oct-20	A	100 %	\$ 5,200	\$ 10,400	\$ 0	\$ 0
WHITNEY	4213798	2007-Feb-14	2010-May- 19	A	100 %	\$ 3,200	\$ 3,200	\$ 0	\$ 0
WHITNEY	4213968	2007-Feb-14	2010-May- 19	A	100 %	\$ 800	\$ 800	\$ 0	\$ 0



This survey was completed using the Instrumentation G.D.D IP Receiver and 3.6 kilowatt transmitter system. Specifications for this unit can be found as Appendix A of this report. The following parameters were kept constant throughout the survey.

Line spacing 100 meters
Station spacing 25 meters
Reading intervals 25 meters
IP method Time domain
IP array Pole-Dipole
Delay time 240Ms

Timing 80Ms through 20 windows

Number of electrodes 6 stainless steel Electrode spacing 25 meters


Parameters measured Chargeability and Apparent Resistivity

Once the IP survey was completed the data was then plotted as individual line pseudosections, one section for each line read, at a scale of 1:2500. These sections show the contoured results for the collected Chargeabilities and Resistivities. Interpretations for any and all conductive zones were then put on each section along with corresponding resistivity high correlations. The data was then correlated to the results of the magnetic and VLF-EM surveys

Copies of these colored contoured and profiled sections are included in the back pocket of this report.

PROPERTY GEOLOGY:

The property is underlain by mafic to intermediate metavolcanics that has been intruded by ultamafic intrusive rocks in the central west section of the grid and eastern central portion of the grid. The host rocks have also been intruded by mafic intrusives along the northwestern and central north sections of the grid area.



MAGNETIC AND VLF-EM SURVEY RESULTS, 2010:

The magnetic and VLF-EM surveys were successful in locating and outlining the geological characteristics of the grid area. Generally the strike of the underlying geology is slightly east, northeast to west, southwest. Several areas of magnetic intensity were noted across the grid area and these zones have good VLF zones associated with them. The most predominant magnetic feature is the strong magnetic high trend that covers most of the central and southwest section of the grid. This trend correlates to the Ultramafic intrusive that is known to come into the grid in this area. The VLF zones correlate well to the edges of the strongest portions of this intrusive as is expected. There are several magnetic highs along strike with this main high. One covers line 1200ME to 1700ME between 350MN and 300MN and it has VLF zones correlating to its edges. Another of these highs lies between 1300ME and 1600ME from the base line to 150MN and a third lies between lines 1800ME and 2300ME and appears to be the eastern extension of the main zone.

The magnetic high that covers the northern sections of the grid from line 0+00 to 1800ME correlates to the mafic intrusive that is thought to cover this section of the grid. Again the VLF zones appear to correlate to the edges of the intrusive. The intrusives appear to be near vertical to slightly south dipping.

There are several minor narrow magnetic trend that appear to parallel the main features which may relate to the ultramafic intrusive and they have VLF zones associated with their edges as well.

There appears to be a minor and or deep narrow magnetic high trend striking into the grid in a southeast direction across lines 1600ME at the south end to line 2200ME at the base line. This zone has a VLF zone paralleling its southern edge from line 1600ME to 1800ME. The trend appears to continue off of the grid to the southwest possibly extending as far as the southern end of line 1300ME.

IP SURVEY RESULTS:

The IP survey was successful in locating and outlining several good conductive zones across the survey area. These zone all seem to correlate well with the strike of the magnetic and VLF-EM horizons.

The most predominant IP zone outlined is a well defined chargeability high that strikes across lines 0+00 to and including line 1500ME and correlates well to the magnetic high that is thought to relate to the ultramafic intrusive. The zone represents a good anomaly that correlates to a moderate to strong resistivity high that has an associated and north flanking resistively low. The zone seems to either deepen and or weaken on its eastern extension as it cuts across lines 1400ME and 1500ME. This may be due in part to the possibility of a northeast and or northwest striking cross structure that appears to have offset the magnetic high.

This main IP trend appears to then strike into a zone that correlates to a magnetic trend that strikes northwest to southeast across lines 1700ME to 1200ME from 200MN to 400MN.

There is an IP anomaly correlating to this magnetic trend and it can be traced from line 1400ME to 1800ME. The zone is a moderate to strong zone that correlates to a modest to weak resistively high-low unit representing a possible contact and or fault zone.

This northwest to southeast striking magnetic high appears to be cut off on its eastern section by a possible cross structure striking northeast. The high then can be traced from line 1800ME to 2300ME from 200MN to 75MN. This magnetic trend may extend as far as line 1200ME on its western extension but again possibly offset by a northeast striking cross structure.

There is a moderate to strong IP anomaly associated with the southern edge of this magnetic high that also correlates to a moderate resistivity high.

A short IP zone appears to strike southwest off of this zone and strikes across lines 2200ME and 2100ME. The zone runs along the eastern edge of a modest magnetic high and appears to truncate next to the suspected northwest striking cross structure. The zone has a correlating resistivity high.

A modest IP anomaly was noted striking into the grid from the east and striking across lines 2700ME to 2600ME south of the base line. This zone is a modest to strong zone that follows the northern edge of a magnetic high and it has an associated modest resistively high.

Another IP zone was noted striking across lines 1300ME to 1000ME from 50MN to 100MS. This zone correlates to a moderate magnetic high on its eastern extension and runs along the northern contact of a spotty magnetic high on its western extension. This zone is a modest anomaly that has an associated resistivity high.

There are several shorter and weaker IP zones scattered across the remainder of the grid that are considered as low priority at this writing but should any of the more predominant zones return encouraging results then they would have to be re-evaluated.

CONCLUSIONS AND RECOMMENDATIONS:

The IP surveys were successful in locating and outlining a number of conductive zones across the grid area that generally correlate directly to the intrusive and or to the edges of the magnetic high trends. The most predominant zone correlates directly to the intrusive. It appears to be shallow and may be exposed along its strike length. The magnetic trends along strike of this main zone as well as offset to the northeast and south of the main zone may be indicative of at least two suspected cross structures. These cross structures appear to strike northeast and northwest and possibly centered on line 1600ME and 1700ME at about 100MN. Both of these structures appear to have interrupted the strike of the IP zones as well.

The primary target area for follow up surveys and or drilling would be in the area of the junction of these two cross structures or between lines 1200ME and 1800ME from 100MS to 400MN.

These IP, magnetic and VLF-EM survey results should be correlated to the elevated gold assay results that were noted in the soil sampling program. Should any of the IP and magnetic zones correlate to the gold areas then a drill program should be considered to test the anomalies at depth.

Respectfully submitted:

J. C. Grant, CET, FGAC

May 2010.

CERTIFICATION

I, John Charles Grant, of 108 Kay Crescent, in the City of Timmins, Province of Ontario, hereby certify that:

- 1). I am a graduate of Cambrian College of Applied Arts and Technology, 1975, Sudbury Ontario Campus, with a 3 year Honors Diploma in Geological and Geophysical Technology.
- I have worked subsequently as an Exploration Geophysicist for Teck Exploration Limited, (5 years, 1975 to 1980), and currently as Exploration Manager and Chief Geophysicist for Exsics Exploration Limited, since May, 1980.
- 3). I am a member in good standing of the Certified Engineering Technologist Association, (CET), since 1984.
- 4). I am in good standing as a Fellow of the Geological Association of Canada, (FGAC), since 1986.
- 5). I have been actively engaged in my profession since the 15th day of May, 1975, in all aspects of ground exploration programs including the planning and execution of field programs, project supervision, data compilation, interpretations and reports.
- 6). I have no specific or special interest nor do I expect to receive any such interest in the herein described property. I have been retained by the property holders and or their Agents as a Geological and Geophysical Consultant and Contract Manager.

John Charles Grant, CET., FGAC.
















Canadian Manufacturer of Geophysical Instrumentation since 1976 Sales, Rental, Customer Service, R&D and Field training

WWW.GDD.CA

32 Channels IP Receiver Model GRx8-32

«Field users have reported that the GDD IP Receiver provided more repeatable readings than any other time domain IP receiver and it read a few additional dipoles.»



Features

- 8 channels expandable to 16, 24 or 32
- Reads up to 32 ch. simultaneously in poles or dipoles
- PDA menu-driven software / simple to use
- 32 channels configuration allows 3D Survey:
 4 lines X 8 channels 2 lines X 16 channels or
 1 line X 32 channels
- Link to a PDA by Bluetooth or RS-232 port
- Real-time data and automatic data stacking (Full Wave)
- Screen-graphics: decay curves, resistivity, chargeability
- · Automatic SP compensation and gain setting
- 20 programmable chargeability windows
- · Survey capabilities: Resistivity and Time domain IP
- One 24 bit A/D converter per channel
- Gain from 1 to 1,000,000,000 (108)
- Shock resistant, portable and environmentally sealed

GRx8-32: This new receiver is a compact and low consumption unit designed for high productivity Resistivity and Induced Polarization surveys. It features high ruggedness allowing to work in any field conditions

Reception poles/dipoles: 8 simultaneous channels expandable to 16, 24 or 32,

for dipole-dipole, pole-dipole or pole-pole arrays.

Programmable windows: The GRx8-32 offers twenty fully programmable windows for a higher flexibility in the definition of the IP decay curve.

User modes available: Arithmetic, logarithmic, serni-logarithmic, Cole-Cole, IPR-12 and user define.

IP display: Chargeability values, Resistivity values and IP decay curves can be displayed in real time. The GRx8-32 can be used for monitoring the noise level and checking the primary voltage waveform.

Internal memory: The memory of 64 megabytes can store 64,000 readings. Each reading totalizes one kilobyte and includes the full set of parameters characterizing the measurements on 8 channels. The data is stored in flash memories not requiring any lithium battery for safeguard. A flash card stores the full wave signal for post-treatment processing.

SPECIFICATIONS

Number of channels: 8, expandable to 16, 24 or 32 Survey capabilities: Resistivity and Time domain IP

Twenty chargeability windows: Anthmetic, logarithmic, semi-

logarithmic, IPR-12 and user defined

Synchronization: Automatic re-synchronization process on primary

voltage signal

Noise reduction: Automatic stacking number **Computation:** Apparent resistivity, chargeability,

standard deviation, and % of symetrical Vp

Size: 41 X 33 X 18 cm (16 X 13 X 7 in) Weight (32 channels): 8.9 kg (19.6 lb)

Enclosure: Heavy-duty Pelican case, environmentally sealed Serial ports: RS-232 and Bluetooth to communicate with a PDA

Temperature range: -45 to +60°C (-49 to +140°F)

Humidity range: Waterproof

POWER

Power: -12 V rechargeable batteries.
-Standard plug for external battery.



Components included with GDD IP Receiver GRx8-32

ned ary

PDA included with GRx8-32

Standard Juniper - Allegro CX mobile PDA computer provided

with the GDD receiver with all accessories.

Operating system: Windows CE

Comes with Bluetooth and RS-232

ELECTRICAL CHARACTERISTICS

Ground Resistance: Up to 1.5 $M\Omega$

Signal waveform: Time domain (ON+, OFF, ON-, OFF)

Time base: 0.5, 1, 2, 4 and 8 seconds

Input impedance: 104 GΩ

Primary voltage: ±10 uV to ±15 V for any channel


Input: True differential for common-mode rejection in dipole configuration

Voltage measurement: Resolution 1 µV

SP offset adjustment: ± 5 V, automatic compensation through linear drift correction per steps of 150 µV

Filter: Eight-pole Bessel low-pass 15 Hz, notch filter 50 Hz and 60 Hz

32 channels GDD GRx8-32 IP Receiver



Α	1x	Not shown but included: Receiver	L	1x	Allegro Cx hand strap	П
В	1x	Not shown but included: Transportation box	М	2x	Allegro Cx NIMH battery pack 3000mAh 3.6V	ı
С	1x	GRx8-32 IP receiver wall charger (120-240V)	N	1x	Allegro Cx external NIMH 3000mAh 3.6V battery charger (120-240V)	ı
D		Red cable banana/alligator (8 ch/10x, 16 ch/19x, 24 ch/28x, 32 ch/37x)	0	1x	Allegro Cx utility CD	ı
Ε	2x	Black cable banana/alligator	Р	1x	Allegro Cx AA alkaline battery holder	ı
F	1x	Allegro Cx field computer	Q	1x	Charger with 4 AA 2400mAh 1.2V NIMH batteries	ı
G	1x	Allegro Cx wall charger (120-240V)	R	1x	Allegro Cx USB power dock	ı
Н	1x	Serial communication cable 9 pos. D-SUB female - 9 pos. D-SUB female	S	1x	Allegro Cx USB cable for USB power dock	ı
1	2x	Serial communication cable 9 pos. D-SUB female - 5 pos. Amphenol male	Ť	tx	Not shown but included: Instruction manual (Receiver)	ı
K	1x	Allegro Cx shoulder strap	U	tx	Not shown but included: Instruction manual (Allegro Cx mobile PDA)	ı
						ı

PURCHASE

Can be shipped anywhere in the world.

RENTAL – available in Canada and USA only

Starts on the day the instrument leaves GDD office in Quebec to the day of its return in GDD office. 50% of the rental fees up to a maximum of 4 months can be credited towards the purchased of the rented instrument.

WARRANTY

All GDD instruments are covered by a one-year warranty. All repairs will be done free of charge at our office in Quebec, Quebec, Canada.

SERVICE

If an instrument manufactured by GDD breaks down while under warranty or service contract, it will be replaced free of charge during repairs (upon request and subject to instruments availability).

OTHER COSTS

Shipping, insurances, customs and taxes are extra if applicable.

PAYMENT

Checks, credit cards, bank transfer, etc.



3700, boul. de la Chaudière, suite 200 Québec (Quèbec), Canada G1X 4B7 Phone: +1 (418) 877-4249

Fax: +1 (418) 877-4054 E-Mail: gdd@gddinstrumentation.com Web Site: www.gddinstrumentation.com

Specifications are subject to change without notice Printed in Quebec, Canada, 2008










Canadian Manufacturer of Geophysical Instrumentation since 1976 Sales, Rental, Customer Service, R&D and Field training

Induced Polarization Transmitter

TxIII-1800W-2400V-10A Model

TxII-3600W-2400V-10A Model





New feature: link two GDD 1800W or 3600W IP TX together and double the voltage (4800V) and power.

Its high power combined with its light weight and a Honda generator makes it particularly suitable for dipole-dipole Induced Polarization surveys.

- Protection against short circuits even at zero (0) ohm
- Output voltage range: 150 V 2400 V / 14 steps
- Power source: 120 V Optional: 220 V, 50 / 60 Hz
- Displays electrode contact, transmitting power and current
- One-year warranty on parts and labour


This backpackable 1800 watts Induced Polarization (I.P.) transmitter works from a standard 120 V source and is well adapted to rocky environments where a high output voltage of up to 2400 volts is needed. Moreover, in highly conductive overburden, at 150 V, the highly efficient TxII-1800W transmitter is able to send current up to 10 A. By using this I.P. transmitter, you obtain fast and high-quality I.P. readings even in the worst conditions. Link two GDD 1800 W IP TX together and transmit up to 3600 watts – 4800 volts – 10 amps.

Face plate of the ←1800W and 3600W→1P Tx

Its high power combined with a Honda generator makes it particularly suitable for pole-dipole Induced Polarization surveys.

- Protection against short circuits even at zero (0) ohm
- Output voltage range: 150 V 2400 V / 14 steps
- Power source: 220 V, 50 / 60 Hz standard 220 V generator
- Displays electrode contact, transmitting power and current
- One-year warranty on parts and labour

This 3600 watts Induced Polarization (I.P.) transmitter works from a standard 220 V source and is well adapted to rocky environments where a high output voltage of up to 2400 volts is needed. Moreover, in highly conductive overburden, at 350 V, the highly efficient TxII-3600W transmitter is able to send current up to 10 A. By using this I.P. transmitter, you obtain fast and high-quality I.P. readings even in the most difficult conditions. Link two GDD 3600 W IP TX together and transmit up to 7200 watts – 4800 volts – 10 amps.



SPECIFICATIONS

TxII-1800W

- Size: 50cm x 30.5cm x 45.7 cm
- Weight: approximately 28 kg
- Operating temperature: -40 °C to 65 °C

ELECTRICAL CHARACTERISTICS

TxII-1800W and TxII-3600W

- Standard time base of 2 seconds for time-domain: 2 seconds ON, 2 seconds
- Optional time base: DC, 0.5, 1, 2, 4 or DC, 1, 2, 4, 8 seconds
- Output current range: 0.030 to 10 A (normal operation)
 0.000 to 10 A (cancel open loop)
- Output voltage range: 150 to 2400 V / 14 steps
- Ability to link 2 GDD Tx to double power using optional Master / Slave cable

CONTROLS

TxII-1800W and TxII-3600W

- Power ON/OFF
- Output voltage range switch: 150 V, 180 V, 350 V, 420 V, 500 V, 600 V, 700 V, 840 V, 1000 V, 1200 V, 1400 V, 1680 V, 2000 V, 2400 V

DISPLAYS

TxII-1800W and TxII-3600W - now 2 displays

- Output current LCD: reads to ± 0.0010 A.
- Electrode contact displayed when not transmitting.
- Output power displayed when transmitting.
- Automatic thermostat controlled LCD heater for read-out.
- Total protection against short circuits even at zero (0) ohm.
- Indicator lamps in case of overload:
 - -High voltage ON/OFF
- -Output overcurrent
- -Generator over or undervoltage
- -Overheating

-Logic fail

-Open Loop Protection

POWER Txil-1800W

Recommended generator:


- Standard 120 V / 60 Hz backpackable Honda generator
- Suggested models: Honda EU1000iC, 1000 W, 13.5 kg or Honda EU2000iC, 2000 W, 21.0 kg

DESCRIPTION TxII-1800W

- Includes shipping box, instruction manual and 110 V plug
- Optional backpackable Tx frame, Master / Slave optional cable

TxII-3600W

- Size: 51 X 41.5 X 21.5 cm built in transportation box from Pelican
- Weight: approximately 32 kg
- Operating temperature: -40 °C to 65 °C



TxII-3600W

Recommended generator:

- Standard 220 V, 50 / 60 Hz Honda generator
- Suggested models: EM3500XK1C, 3500 W, 62 kg or EM5000XK1C, 5000 W, 77 kg

TxII-3600W

- Includes built-in shipping box, instruction manual and 220 V plug
- Optional 220 V extension, Master / Slave optional cable

PURCHASE

Can be shipped anywhere in the world.

RENTAL - available in Canada and USA only

Starts on the day the instrument leaves GDD office in Quebec to the day of its return in GDD office. 50% of the rental fees up to a maximum of 4 months can be credited towards the purchased of the rented instrument.

WARRANTY

All GDD instruments are covered by a one-year warranty. All repairs will be done free of charge at our office in Quebec, Quebec, Canada.

OTHER COSTS

Shipping, insurances, customs and taxes are extra if applicable. PAYMENT

Checks, credit cards, bank transfer, etc

SERVICE

If an instrument manufactured by GDD breaks down while under warranty or service contract, it will be replaced free of charge during repairs (upon request and subject to instruments availability).



3700, boul. de la Chaudière, suite 200

Québec (Québec) Canada G1X 4B7 Phone: +1 (418) 877-4249 Fax: +1 (418) 877-4054

E-Mail: gdd@qddinstrumentation.com
Web Site: www.qddinstrumentation.com

Specifications are subject to change without notice Printed in Quebec, Canada, 2008

