



41014SE0009 20 LACKNER

010

Diamond Drilling

Township of LACKNER

Report NO: 20

Work performed by: APAMAG MINES LTD.

Claim NO	Hole NO	Footage	Date	Note
S 74694	# 2	287'	Jan/55	

Notes:

DIAMOND DRILL RECORD

HOLE NO. 2

PROPERTY **APANG MINES LIMITED, LACKNER TOWNSHIP**

SHEET NO. **1**

DATE **March 19, 1955**

Dip Angles Collar - 90°	Bearing None	Latitude 250' North No. 2 Post	Started January 23, 1955
90° - 80°	Length 237'	Departure 125' West No. 2 Post	Stopped February 5, 1955
280° - 70°	Location Claim No. 8-7469A	Elevation	Logged by W.L. Angus

ROCK			CORE SAMPLES				SLUDGE SAMPLES		
Footage	Name of Rock	DESCRIPTION	Footage	Description	Width	Assay TA, CB	Footage	Width	Assay
0'-108'	Casing	Overburden, sand, gravel, boulders.							
108'-168'	Quartz diabase.	Medium grained, some feldspar & quartz. From 136'-149', Fine grained, less quartz, with muscovite & porphyritic in places. At 149', becomes medium grained at carbonate contact 25' to core.							
168'-168.3'	Granite	Intrusive, tongue cutting core at 40'							
168'-181.5'	Quartz diabase.	From 172.5'-173.5' minor amounts of green epidote with minute specks of resin- like yellow mineral. Also found in 2" band of fine grained diabase at 173.5'	172.5'-173.5'	Sample 14307	1'.0'				
181.5'-188.5'	Diabase	Fine grained uniform dark rock.							
188.5'-262.5'	Granite	Sharp contact at 188.5' 60° to core, light coloured pinkish rock. At 228' - 3 inch calcite vein structure 50° to core. Core lost 232'-233.5'							
262.5'-287'	Horblende Granite.	Contact gradual over 3 1/2 feet. Dark blotchy rock, coarse to medium grained with spots of horblende, some quartz. Core stored at Apang office in Baillybury, Ontario.							


N.M.P.

No. 4

Claim No. S-74694



D.D.H. NO 2
280'
90°



No. 2

No. 3