



42C04SE880 41N13NE-0014 PILOT HARBOUR

010

REPORT ON
COMBINED HELICOPTER-BORNE
MAGNETIC, ELECTROMAGNETIC,
AND VLF-EM SURVEY
PUKASWA RIVER CLAIMS
ONTARIO

RECEIVED

NOV 1 1983

MINING LANDS SECTION

for
COTTON VALLEY RESOURCES LIMITED
by
AERODAT LIMITED
JUNE 1983



42C04SE8880 41N13NE-0014 PILOT HARBOUR

010C

TABLE OF CONTENTS

	<u>Page No.</u>
1. INTRODUCTION	1 - 1
2. SURVEY AREA/CLAIM NUMBERS AND LOCATIONS	2 - 1
3. AIRCRAFT EQUIPMENT	3 - 1
3.1 Aircraft	3 - 1
3.2 Equipment	3 - 1
3.2.1 Electromagnetic System	3 - 1
3.2.2 VLF-EM	3 - 1
3.2.3 Magnetometer	3 - 2
3.2.4 Magnetic Base Station	3 - 2
3.2.5 Radar Altimeter	3 - 2
3.2.6 Tracking Camera	3 - 3
3.2.7 Analog Recorder	3 - 3
3.2.8 Digital Recorder	3 - 4
4. DATA PRESENTATION	4 - 1
4.1 Base Map and Flight Path Recovery	4 - 1
4.2 Electromagnetic Profile Maps	4 - 2
4.3 Magnetic Contour Maps	4 - 4
4.4 VLF-EM Contour Maps	4 - 5
4.5 Electromagnetic Survey Conductor Symbolization	4 - 6
4.6 Interpretation Maps	4 - 8
APPENDIX I - General Interpretive Considerations	

LIST OF MAPS

(Scale: 1/15,840)

- | | |
|-------|--|
| Map 1 | Interpreted Conductive Units |
| Map 2 | Airborne Electromagnetic Survey Profile Map
(955 Hz. coaxial) |
| Map 3 | Total Field Magnetic Map |
| Map 4 | VLF-EM Total Field Contours |

Data provided but not included in report:

- 1 - master map (2 colour) of coaxial and coplanar profiles with flight path
- 2 - anomaly list providing estimates of depth and conductivity thickness
- 3 - analogue records of data obtained in flight

1. INTRODUCTION

This report describes an airborne geophysical survey carried out on behalf of Cotton Valley Resources Limited by Aerodat Limited. Equipment operated included a 3 frequency electromagnetic system, a VLF-EM system, and a magnetometer.

The survey was flown on March 3 to March 22, 1983 from an operations base at Wawa Ontario. A total of 1019 line miles were flown, at a nominal line spacing of 660 feet. Of the total flown, this report describes 500 line miles.

2. SURVEY AREA/CLAIM NUMBERS AND LOCATIONS

The mining claim numbers and locations covered by this survey are indicated on the map in the following pocket.

3. AIRCRAFT EQUIPMENT

3.1 Aircraft

The helicopter used for the survey was an Aerospatial Astar 350D owned and operated by North Star Helicopters. Installation of the geophysical and ancillary equipment was carried out by Aerodat. The survey aircraft was flown at a nominal altitude at 60 meters.

3.2 Equipment

3.2.1 Electromagnetic System

The electromagnetic system was an Aerodat/ Geonics 3 frequency system. Two vertical coaxial coil pairs were operated at 955 and 4130 Hz and a horizontal coplanar coil pair at 4500 Hz. The transmitter-receiver separation was 7 meters. In-phase and quadrature signals were measured simultaneously for the 3 frequencies with a time-constant of 0.1 seconds. The electromagnetic bird was towed 30 meters below the helicopter.

3.2.2 VLF-EM System

The VLF-EM System was a Herz 2A. This instrument measures the total field and vertical

quadrature component of two selected frequencies. The sensor was towed in a bird 15 meters below the helicopter.

The sensor aligned with the flight direction is designated as "LINE", and the sensor perpendicular to the line direction as "ORTHO". The "LINE" station used was NAA, Cutler Maine, 17.8 KHz or NLK, Jim Creek Washington, 24.8 KHz. The "ORTHO" station was NSS, Annapolis Maryland, 21.4 KHz. The NSS transmitter was operating on a very limited schedule and was not available during a large part of the survey.

3.2.3 Magnetometer

The magnetometer was a Geometrics G-803 proton precession type. The sensitivity of the instrument was 1 gamma at a 1.0 second sample rate. The sensor was towed in a bird 15 meters below the helicopter.

3.2.4 Magnetic Base Station

An IFG proton precession type magnetometer was operated at the base of operations to record diurnal variations of the earths magnetic field. The clock of the base station was synchronized with that of the airborne system

to facilitate later correlation.

3.2.5 Radar Altimeter

A Hoffman HRA-100 radar altimeter was used to record terrain clearance. The output from the instrument is a linear function of altitude for maximum accuracy.

3.2.6 Tracking Camera

A Geocam tracking camera was used to record flight path on 35 mm film. The camera was operated in strip mode and the fiducial numbers for cross reference to the analog and digital data were imprinted on the margin of the film.

3.2.7 Analog Recorder

A RMS dot-matrix recorder was used to display the data during the survey. A sample record with channel identification and scales is presented on the following page.

ANALOG CHART

CAMERA
FIDUCIAL #

1000 1010 1020

TIME

MAG

20 gamma

ALTIMETER

20 feet

0 feet

VLF QUAD.

(ORTHO)

VLF TOTAL

25%

VLF QUAD.

(LINE)

VLF TOTAL

COPLANAR QUAD.

40 ppm.

COPLANAR IN-PHASE

40 ppm.

COAXIAL QUAD.
(HIGH FREQ.)

20 ppm.

COAXIAL IN-PHASE
(HIGH FREQ.)

20 ppm.

COAXIAL QUAD.
(LOW FREQ.)

20 ppm.

COAXIAL IN-PHASE
(LOW FREQ.)

20 ppm.

MAG

50 gammas

MANUAL FIDUCIAL

0040

0041

0042

0043

0044

3.2.8 Digital Recorder

A Perle DAC/NAV data system recorded the survey data on cassette magnetic tape. Information recorded was as follows:

<u>Equipment</u>	<u>Interval</u>
EM	0.1 second
VLF-EM	0.5 second
magnetometer	0.5 second
altimeter	1.0 second
fiducial (time)	1.0 second
fiducial (manual)	0.2 second

4. DATA PRESENTATION

4.1 Base Map and Flight Path Recovery

The base map photomosaic at a scale of 1/15,840 was constructed from available aerial photography. The flight path was plotted manually on this base and digitized for use in the computer compilation of the maps. The flight path is presented with fiducials for cross reference to both the analog and digital data.

4.2 Electromagnetic Profile Maps

The electromagnetic data was recorded digitally at a high sample rate of 10/second with a small time constant of 0.1 second. A two stage digital filtering process was carried out to reject major spheric events, and reduce system noise.

Local atmospheric activity can produce sharp, large amplitude events that cannot be removed by conventional filtering procedures. Smoothing or stacking will reduce their amplitude but leave a broader residual response that can be confused with a geological phenomenon. To avoid this possibility, a computer algorithm searches out and rejects the major "spheric" events.

The signal to noise was further enhanced by the application of a low pass filter. The filter was applied digitally. It has zero phase shift which prevents any lag or peak displacement from occurring and it suppresses only variation with a wavelength less than about 0.25 seconds. This low effective time constant permits maximum profile shape resolution.

Following the filtering processes, a base level correction was made. The correction applied is a linear function of time that ensures that the corrected amplitude of the various inphase and quadrature components

is zero when no conductive or permeable source is present. This filtered and levelled data was then presented in profile map form.

The in-phase and quadrature responses of the coaxial 955 Hz configuration are plotted with the flight path and presented on the photomosaic base.

The in-phase and quadrature responses of the coaxial 4500 Hz and the coplanar 4130 Hz configuration are plotted with flight path and are available as a two colour overlay.

4.3 Magnetic Contour Maps

The aeromagnetic data was corrected for diurnal variations by subtraction of the digitally recorded base station magnetic profile. No correction for regional variation is applied.

The corrected profile data was interpolated onto a regular grid at a 2.5 mm interval using a cubic spline technique. The grid provided the basis for threading the presented contours at a 10 gamma interval.

4.4 VLF-EM Contour and Profile Maps

The VLF-EM "LINE" signal, was compiled in map form. The mean response level of the total field signal was removed and the data was gridded and contoured at an interval of 2%. When the "ORTHO" signal was available it was compiled in a similar fashion.

4.5 Electromagnetic Conductor Symbolization

The electromagnetic profile maps were used to identify those anomalies with characteristics typical of bedrock conductors. The in-phase and quadrature response amplitudes at 4130 Hz were digitally applied to a phasor diagram for the vertical half-plane model and estimates of conductance (conductivity thickness) were made. The conductance levels were divided into categories as indicated in the map legend; the higher the number, the higher the estimated conductivity thickness product.

As discussed in Appendix I the conductance should be used as a relative rather than absolute guide to conductor quality. A conductance value of less than 2 mhos is typical for conductive overburden material and electrolytic conductors in faults and shears. Values greater than 4 mhos generally indicate some electronic conduction by certain metallic sulphides and/or graphite. Gold, although highly conductive, is not expected to occur in sufficient concentration to directly produce an electromagnetic anomaly; however, accessory mineralization such as pyrite or

graphite can produce a measurable response.

With the aid of the profile maps, responses of similar characteristics may be followed from line to line and conductor axes identified.

The distinction between conductive bedrock and overburden anomalies is not always clear and some of the symbolized anomalies may not be of bedrock origin. It is also possible that a response may have been mistakenly attributed to overburden and therefore not included in the symbolization process. For this reason, as geological and other geophysical information becomes available, reassessment of the significance of the various conductors is recommended.

4.6 INTERPRETATION MAPS

The conductive trends are shown and discriminated for descriptive purposes.

These conductors are described below:


- 1 Moderate conductor with coincident weak magnetic response. At granite contact.
- 2 Moderate, short, magnetic conductor, in rhyolite
- 3 Weak conductor with associated magnetic high
- 4 Weak to moderate bedrock conductor divided by diabase dyke, response modified by conductive lake bottom
- 5 Fair to good conductor mapped as rhyolite/andesite contact
- 6 Weak conductor on south flank of iron formation
- 7 Weak conductor in iron formation
- 8 Moderate to fair short conductor on south flank of iron formation

- 9 Good multiple conductor on rhyolite/andesite contact
- 10 Moderate conductor next to iron formation
- 11 Weak, formational conductor on north flank of iron formation
- 12 Weak conductor associated with iron formation
- 13 Moderate conductor following topographic low
- 14 Variable weak to fair conductor mapped as andesite
- 15 Short, definite conductor near copper showing on greenstone/granite contact
- 16 Isolated short, weak conductor in greenstone
- 17 Weak conductor in magnetic low
- 18 Fair magnetic conductor near volcanic/sediment contact.
- 19 Weak to moderate conductor near volcanic/sediment contact
- 20 Moderate conductor similar to 19
- 21 Isolated, weak, one-line conductivity on magnetic high

- 22 Weak conductor in sediments
- 23 Weak multiple conductor in sediments
- 24 Weak conductor in sediments
- 25 Weak conductor may be overburden
- 26 Weak to moderate linear conductor, no outcrop mapped.
- 27 Weak conductor associated with magnetic high near granite contact.
- 28 Weak magnetic conductor near volcanic/sediment contact
- 29 Weak conductor near contact
- 30 Short weak probable conductor next to diabase dyke
- 31 Short fair isolated bedrock
- 32 Short conductor on magnetic high
- 33 Poor, long conductor, probably overburden
- 34 High amplitude, poor conductivity responses, probably related to lake bottom sediments

35 Weak responses next to diabase dyke,
probably bedrock.

Respectfully submitted,

A handwritten signature in cursive script, appearing to read "Fenton Scott".

Fenton Scott, P. Eng.

JUNE 29, 1983.

APPENDIX I

GENERAL INTERPRETIVE CONSIDERATIONS

Electromagnetic

The Aerodat 3 frequency system utilizes 2 different transmitter-receiver coil geometries. The traditional coaxial coil configuration is operated at 2 widely separated frequencies and the horizontal coplanar coil pair is operated at a frequency approximately aligned with one of the coaxial frequencies.

The electromagnetic response measured by the helicopter system is a function of the "electrical" and "geometrical" properties of the conductor. The "electrical" property of a conductor is determined largely by its conductivity and its size and shape; the "geometrical" property of the response is largely a function of the conductors shape and orientation with respect to the measuring transmitter and receiver.

Electrical Considerations

For a given conductive body the measure of its conductivity or conductance is closely related to the measured phase shift between the received and transmitted electromagnetic field. A small phase shift indicates a relatively high conductance, a large phase shift lower conductance. A small phase shift results in a large in-phase to quadrature

ratio and a large phase shift a low ratio. This relationship is shown quantitatively for a vertical half-plane model on the accompanying phasor diagram. Other physical models will show the same trend but different quantitative relationships.

The phasor diagram for the vertical half-plane model, as presented, is for the coaxial coil configuration with the amplitudes in ppm as measured at the response peak over the conductor. To assist the interpretation of the survey results the computer is used to identify the apparent conductance and depth at selected anomalies. The results of this calculation are presented in table form in Appendix I and the conductance and in-phase amplitude are presented in symbolized form on the map presentation.

The conductance and depth values as presented are correct only as far as the model approximates the real geological situation. The actual geological source may be of limited length, have significant dip, its conductivity and thickness may vary with depth and/or strike and adjacent bodies and overburden may have modified the response. In general the conductance estimate is less affected by these limitations than the depth estimate but both should be considered a relative rather than absolute guide to the anomalies properties.

Conductance in mhos is the reciprocal of resistance in ohms and in the case of narrow slab like bodies is the product of electrical conductivity and thickness.

Most overburden will have an indicated conductance of less than 2 mhos; however, more conductive clays may have an apparent conductance of say 2 to 4 mhos. Also in the low conductance range will be electrolytic conductors in faults and shears.

The higher ranges of conductance, greater than 4 mhos, indicate that a significant fraction of the electrical conduction is electronic rather than electrolytic in nature. Materials that conduct electronically are limited to certain metallic sulphides and to graphite. High conductance anomalies, roughly 10 mhos or greater are generally limited to sulphide or graphite bearing rocks.

Sulphide minerals with the exception of sphalerite, cinnabar and stibnite are good conductors; however, they may occur in a disseminated manner that inhibits electrical conduction through the rock mass. In this case the apparent conductance can seriously under rate the quality of the conductor in geological terms. In a similar sense the relatively non-conducting sulphide minerals noted above may be present in significant concentration in association with minor conductive

sulphides, and the electromagnetic response only relate to the minor associate mineralization. Indicated conductance is also of little direct significance for the identification of gold mineralization. Although gold is highly conductive it would not be expected to exist in sufficient quantity to create a recognizable anomaly but minor accessory sulphide mineralization could provide a useful indirect indication.

In summary the estimated conductance of a conductor can provide a relatively positive identification of significant sulphide or graphite mineralization; however, a moderate to low conductance value does not rule out the possibility of significant economic mineralization.

Geometrical Considerations

Geometrical information about the geologic conductor can often be interpreted from the profile shape of the anomaly. The change in shape is primarily related to the change in inductive coupling among the transmitter, the target, and the receiver.

In the case of a thin, steeply dipping, sheet-like conductor, the coaxial coil pair will yield a near symmetric peak over the conductor. On the other hand the coplanar coil pair will pass through a null couple relationship and yield a minimum over the conductor, flanked by positive side lobes. As the dip of the conductor decreases from vertical, the coaxial

anomaly shape changes only slightly, but in the case of the coplanar coil pair the side lobe on the down dip side strengthens relative to that on the up dip side.

As the thickness of the conductor increases, induced current flow across the thickness of the conductor becomes relatively significant and complete null coupling with the coplanar coils is no longer possible. As a result, the apparent minimum of the coplanar response over the conductor diminishes with increasing thickness, and in the limiting case of a fully 3 dimensional body or a horizontal layer or half-space, the minimum disappears completely.

A horizontal conducting layer such as overburden will produce a response in the coaxial and coplanar coils that is a function of altitude (and conductivity if not uniform). The profile shape will be similar in both coil configurations with an amplitude ratio (coplanar/coaxial) of about 4/1.*

In the case of a spherical conductor, the induced currents are confined to the volume of the sphere, but not relatively restricted to any arbitrary plane as in the case of a sheet-like form. The response of the coplanar coil pair directly over the sphere may be up to 8* times greater than that of the coaxial coil pair.

In summary a steeply dipping, sheet-like conductor will display a decrease in the coplanar response coincident with the peak of the coaxial response. The relative strength of this coplanar null is related inversely to the thickness of the conductor; a pronounced null indicates a relatively thin conductor. The dip of such a conductor can be inferred from the relative amplitudes of the side-lobes.

Massive conductors that could be approximated by a conducting sphere will display a simple single peak profile form on both coaxial and coplanar coils, with a ratio between the coplanar to coaxial response amplitudes as high as 8.*

Overburden anomalies often produce broad poorly defined anomaly profiles. In most cases the response of the coplanar coils closely follow that of the coaxial coils with a relative amplitude ratio of 4.*

Occasionally if the edge of an overburden zone is sharply defined with some significant depth extent, an edge effect will occur in the coaxial coils. In the case of a horizontal conductive ring or ribbon, the coaxial response will consist of two peaks, one over each edge; whereas the coplanar coil will yield a single peak.

* It should be noted at this point that Aerodat's definition of the measured ppm unit is related to the primary field sensed in the receiving coil without normalization to the maximum coupled (coaxial configuration). If such normalization were applied to the Aerodat units, the amplitude of the coplanar coil pair would be halved.

Magnetics

The Total Field Magnetic Map shows contours of the total magnetic field, uncorrected for regional variation. Whether an EM anomaly with a magnetic correlation is more likely to be caused by a sulphide deposit than one without depends on the type of mineralization. An apparent coincidence between an EM and a magnetic anomaly may be caused by a conductor which is also magnetic, or by a conductor which lies in close proximity to a magnetic body. The majority of conductors which are also magnetic are sulphides containing pyrrhotite and/or magnetite. Conductive and magnetic bodies in close association can be, and often are, graphite and magnetite. It is often very difficult to distinguish between these cases. If the conductor is also magnetic, it will usually produce an EM anomaly whose general pattern resembles that of the magnetics. Depending on the magnetic permeability of the conducting body, the amplitude of the inphase EM anomaly will be weakened, and if the conductivity is also weak, the inphase EM anomaly may even be reversed in sign.

VLF Electromagnetics

The VLF-EM method employs the radiation from powerful military radio transmitters as the primary signals. The magnetic field associated with the primary field is elliptically polarized in the vicinity of electrical conductors. The Herz Totem uses three coils in the X. Y. Z. configuration to measure the total field and vertical quadrature component of the polarization ellipse.

The relatively high frequency of VLF 15-25 KHz provides high response factors for bodies of low conductance. Relatively "disconnected" sulphide ores have been found to produce measurable VLF signals. For the same reason, poor conductors such as sheared contacts, breccia zones, narrow faults, alteration zones and porous flow tops normally produce VLF anomalies. The method can therefore be used effectively for geological mapping. The only relative disadvantage of the method lies in its sensitivity to conductive overburden. In conductive ground the depth of exploration is severely limited.

The effect of strike direction is important in the sense of the relation of the conductor axis relative to the energizing electromagnetic field. A conductor aligned along a radius drawn from a transmitting station will be

in a maximum coupled orientation and thereby produce a stronger response than a similar conductor at a different strike angle. Theoretically it would be possible for a conductor, oriented tangentially to the transmitter to produce no signal. The most obvious effect of the strike angle consideration is that conductors favourably oriented with respect to the transmitter location and also near perpendicular to the flight direction are most clearly rendered and usually dominate the map presentation.

The total field response is an indicator of the existence and position of a conductivity anomaly. The response will be a maximum over the conductor, without any special filtering, and strongly favour the upper edge of the conductor even in the case of a relatively shallow dip.

The vertical quadrature component over steeply dipping sheet like conductor will be a cross-over type response with the cross-over closely associated with the upper edge of the conductor.

The response is a cross-over type due to the fact that it is the vertical rather than total field quadrature component that is measured. The response shape is due largely to geometrical rather than conductivity considerations and the distance between the maximum and minimum on either side of the cross-over is related to target depth. For a given target geometry, the larger this distance the greater the

depth.

The amplitude of the quadrature response, as opposed to shape is function of target conductance and depth as well as the conductivity of the overburden and host rock. As the primary field travels down to the conductor through conductive material it is both attenuated and phase shifted in a negative sense. The secondary field produced by this altered field at the target also has an associated phase shift. This phase shift is positive and is larger for relatively poor conductors. This secondary field is attenuated and phase shifted in a negative sense during return travel to the surface. The net effect of these 3 phase shifts determine the phase of the secondary field sensed at the receiver.

A relatively poor conductor in resistive ground will yield a net positive phase shift. A relatively good conductor in more conductive ground will yield a net negative phase shift. A combination is possible whereby the net phase shift is zero and the response is purely in-phase with no quadrature component.

A net positive phase shift combined with the geometrical cross-over shape will lead to a positive quadrature response on the side of approach and a negative on the side of departure. A net negative phase shift would produce the reverse. A further sign reversal occurs with a 180 degree

change in instrument orientation as occurs on reciprocal line headings. During digital processing of the quadrature data for map presentation this is corrected for by normalizing the sign to one of the flight line headings.



42C04SE8880 41N13NE-0014 PILOT HARBOUR

900



Ontario

Ministry of Natural Resources

File _____

GEOPHYSICAL - GEOLOGICAL - GEOCHEMICAL
TECHNICAL DATA STATEMENT

TO BE ATTACHED AS AN APPENDIX TO TECHNICAL REPORT
FACTS SHOWN HERE NEED NOT BE REPEATED IN REPORT
TECHNICAL REPORT MUST CONTAIN INTERPRETATION, CONCLUSIONS ETC.

Type of Survey(s) AIRBORNE E.M., MAG., VLF
Township or Area PILOT HARBOUR, DAVID LAKE
Claim Holder(s) COTTON VALLEY RESOURCES
Survey Company AERODAT LIMITED
Author of Report FENTON SCOTT
Address of Author 17 MARA ROAD A. DOW MILLS
Covering Dates of Survey MARCH 3 TO 22 / 1983
(linecutting to office)
Total Miles of Line Cut 480

MINING CLAIMS TRAVERSED
List numerically

SSM 619517 ETAL
(prefix) (number)
(LIST ATTACHED)

RECEIVED
MARCH 1 1983
MINING CLAIMS SECTION

SPECIAL PROVISIONS
CREDITS REQUESTED

ENTER 40 days (includes
line cutting) for first
survey.
ENTER 20 days for each
additional survey using
same grid.

Geophysical
-Electromagnetic _____
-Magnetometer _____
-Radiometric _____
-Other _____
Geological _____
Geochemical _____

DAYS
per claim

AIRBORNE CREDITS (Special provision credits do not apply to airborne surveys)

Magnetometer 20.1 Electromagnetic 20.1 Radiometric 20.1
(enter days per claim)

DATE: Oct 31 / 83 SIGNATURE: Fenton Scott
Author of Report or Agent

Res. Geol. _____ Qualifications 63.1263

Previous Surveys

File No.	Type	Date	Claim Holder

TOTAL CLAIMS 954

OFFICE USE ONLY

SELF POTENTIAL

Instrument _____ Range _____

Survey Method _____

Corrections made _____

RADIOMETRIC

Instrument _____

Values measured _____

Energy windows (levels) _____

Height of instrument _____ Background Count _____

Size of detector _____

Overburden _____

(type, depth - include outcrop map)

OTHERS (SEISMIC, DRILL WELL LOGGING ETC.)

Type of survey _____

Instrument _____

Accuracy _____

Parameters measured _____

Additional information (for understanding results) _____

AIRBORNE SURVEYS

Type of survey(s) MAGNETIC ELECTROMAGNETIC VLF-EM

Instrument(s) GEOMETRICS G803 AERUBAT 3 FREQ. TUTEM 2A

Accuracy 0.5% 1 ppm 1% (1 mm)

(specify for each type of survey)

Aircraft used A-512R HELICOPTER

Sensor altitude 150' 100' 150'

Navigation and flight path recovery method VISUAL NAVIGATION, ON BOARD CAMERA,

MANUAL AND AUTOMATIC FIDUCIALS

Aircraft altitude 200' Line Spacing 660'

Miles flown over total area 1019 Over claims only 480'

Dec. 30th



Report of Work
(Geophysical, Geological,
Geochemical and Expenditures)

25968

Instructions: - Please type or print.
- If number of mining claims traversed
exceeds space on this form, attach a list.
Note: - Only days credits calculated in the
"Expenditures" section may be entered
in the "Expend. Days Cr." columns.
- Do not use shaded areas below.

The Mining Act

Type of Survey(s) Airborne Electromagnetic, Magnetic, VLF-EM				Township or Area Pilot Harbour, David Lake						
Claim Holder(s) Golden Valley Resources, c/o Midnorth Engineering					Prospector's Licence No. A22041					
Address Suite 1205 45 Richmond Street West, Toronto (Agent for - see attached appendix)										
Survey Company Aerodat Limited				Date of Survey (from & to)		Total Miles of line Cut				
				3	3	83	22	3	83	480
Name and Address of Author (of Geo-Technical report) Fenton Scott 17 Malabar Place, Don Mills, Ontario										

Special Provisions	Geophysical		Days per Claim
	Electromagnetic	Magnetometer	
For first survey: Enter 40 days. (This includes line cutting)	- Electromagnetic		
	- Magnetometer		
	- Radiometric		
	- Other		
For each additional survey: using the same grid: Enter 20 days (for each)			
	Geological		Days per Claim
	Geochemical		

Mining Claims Traversed (List in numerical sequence)		
Prefix	Number	Expend. Days Cr.
SSM	619517 et al	
List Attached		

Credits Requested per Each Claim in Columns at right		
Man Days Complete reverse side and enter total(s) here		
Airborne Credits	Electromagnetic	20.1
	Magnetometer	20.1
	Radiometric VLF	20.1
Expenditures (excludes power stripping)		
Type of Work Performed		
Performed on Claim(s)		
Calculation of Expenditure Days Credits		
Total Expenditures	+	15 =
\$		
Instructions Total Days Credits may be apportioned at the claim holder's choice. Enter number of days credits per claim selected in columns at right.		

RECEIVED
NOV 3 1983
MINING LANDS SECTION

BAULT STE MARIE MINING DIV. RECEIVED
OCT 31 1983
A.M. 10 11 12 P.M. 1 2 3 4 5 6

Total number of mining claims covered by this report of work. **954**

Date Oct. 28/83	Recorded Holder or Agent (Signature) <i>[Signature]</i>
---------------------------	--

For Office Use Only		Mining Recorder <i>[Signature]</i>	
Total Days Cr. Recorded 57526.2	Date Recorded Oct 31/83	By the Director <i>[Signature]</i>	

Certification Verifying Report of Work **Cotton Valley**
I hereby certify that I have a personal and intimate knowledge of the facts set forth in the Report of Work annexed hereto, having performed the work or witnessed same during and/or after its completion and the annexed report is true.

Name and Postal Address of Person Certifying Fenton Scott 17 Malabar Place, Don Mills, Ontario M3B 1A4		
Date Certified OCT 28/83	Certified by (Signature) <i>[Signature]</i>	

Recorded Holders of claims listed on attached appendixes

Gerard Couture	K.19803	Fen: Morin	K.19806
Robert Belisle	K. 19802	Daniel Mercier	K.19807
Norman Upham	K.19785	Real Mongeau	K.19808
Gaston Marquis	K.19735	Bernard Paquette	K.19809
Gerald Falardeau	K.19804	David Recoskie	K.19810
Larry Farrell	K.19805	Louis Cyr	K.19831

RECEIVED

NOV 3 1983

MINING LANDS SECTION

REPORT ON THE POYASKWA RIVER PROPERTY, COTTON VALLEY RES. INC.

TABLE I - CLAIM LIST

SSM 619517 ✓	SSM 664217 ✓	SSM 664252 ✓
	" 218 ✓	" 233
619524 ✓	" 219 ✓	" 234
" 525 ✓	" 220 ✓	" 235
" 526 ✓	" 221 ✓	" 236
" 527 ✓	" 222 ✓	" 237
	" 223 ✓	" 238
662185 ✓	" 224 ✓	" 239
" 186 ✓	" 225 ✓	" 240
" 187 ✓	" 226 ✓	" 241
" 188 ✓	" 227 ✓	" 242
" 189 ✓	" 228 ✓	" 243
" 190 ✓	" 229 ✓	" 244
" 191 ✓	" 230 ✓	" 245
" 192 ✓	" 231 ✓	" 246
" 193 ✓	" 232 ✓	" 247
" 194 ✓		" 248
" 195 ✓	664236 ✓	" 249
" 196 ✓	" 237 ✓	" 250
" 197 ✓		" 251
" 198 ✓	664239 ✓	" 252
" 199 ✓	" 240 ✓	" 253 ✓
	" 241 ✓	" 254 ✓
	" 242 ✓	" 255 ✓
664208 ✓	" 243 ✓	" 256 ✓
" 209 ✓	" 244 ✓	" 257 ✓
" 210 ✓	" 245 ✓	" 258 ✓
" 211 ✓	" 246 ✓	" 259 ✓
" 212 ✓	" 247 ✓	" 260 ✓
" 213 ✓	" 248 ✓	" 261 ✓
" 214 ✓	" 249 ✓	" 262 ✓
" 215 ✓	" 250 ✓	" 263 ✓
" 216 ✓	" 251 ✓	" 264 ✓

PUKAWA RIVER PROPERTY CLAIM LIST - Contd.

2.

SSI' 664266 ✓	SSM 664308 ✓	SSM 664349 ✓
" 267 ✓	" 309 ✓	" 350 ✓
" 268 ✓	" 310 ✓	" 351 ✓
" 269 ✓	" 311 ✓	" 352 ✓
" 270 ✓	" 312 ✓	" 353 ✓
" 271 ✓	" 313 ✓	" 354 ✓
" 272 ✓	" 314 ✓	" 355 ✓
" 273 ✓	" 315 ✓	" 356 ✓
" 274 ✓	" 316 ✓	" 357 ✓
" 275 ✓	" 317 ✓	" 358 ✓
" 276 ✓		" 359 ✓
" 277 ✓	664319 ✓	" 360 ✓
" 278 ✓	664322 ✓	" 361 ✓
" 279 ✓	" 323 ✓	" 362 ✓
" 280 ✓	" 324 ✓	" 363 ✓
" 281 ✓	" 325 ✓	" 364 ✓
" 282 ✓		" 365 ✓
" 283 ✓	664327 ✓	" 366 ✓
" 284 ✓		" 367 ✓
" 285 ✓	664330 ✓	" 368 ✓
" 286 ✓	" 331 ✓	" 369 ✓
" 287 ✓	" 332 ✓	" 370 ✓
" 288 ✓	" 333 ✓	" 371 ✓
" 289 ✓	" 334 ✓	" 372 ✓
" 290 ✓		" 373 ✓
" 291 ✓	664336 ✓	" 374 ✓
" 292 ✓	" 337 ✓	" 375 ✓
" 293 ✓	" 338 ✓	" 376 ✓
" 294 ✓	" 339 ✓	" 377 ✓
" 295 ✓	" 340 ✓	" 378 ✓
" 296 ✓	" 341 ✓	" 379 ✓
" 297 ✓	" 342 ✓	" 380 ✓
" 298 ✓		" 381 ✓
" 299 ✓	664345 ✓	" 382 ✓
" 300 ✓	" 346 ✓	" 383 ✓
" 301 ✓	" 347 ✓	" 384 ✓
	" 348 ✓	

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

SSM 664385 ✓
" 386 ✓
" 387 ✓
" 388 ✓
" 389 ✓
" 390 ✓
" 391 ✓
" 392 ✓
" 393 ✓
" 394 ✓
" 395 ✓
" 396 ✓
" 397 ✓
" 398 ✓
" 399 ✓
" 400 ✓
" 401 ✓
" 402 ✓
" 403 ✓
" 404 ✓
" 405 ✓
" 406 ✓
" 407 ✓
" 408 ✓
" 409 ✓
" 410 ✓
" 411 ✓
" 412 ✓
" 413 ✓
" 414 ✓

664416 ✓
" 417 ✓
" 418 ✓
" 419 ✓

SSM 664420 ✓
" 421 ✓
" 422 ✓
" 423 ✓
" 424 ✓
" 425 ✓
" 426 ✓

664428 ✓
" 429 ✓
" 430 ✓
" 431 ✓
" 432 ✓
" 433 ✓

664435 ✓
" 436 ✓
" 437 ✓
" 438 ✓
" 439 ✓
" 440 ✓

664442 ✓
" 443 ✓
" 444 ✓
" 445 ✓
" 446 ✓
" 447 ✓
" 448 ✓
" 449 ✓
" 450 ✓
" 451 ✓
" 452 ✓
" 453 ✓
" 454 ✓
" 455 ✓
" 456 ✓

SSM 664458 ✓
" 459 ✓
" 460 ✓
" 461 ✓
" 462 ✓
" 463 ✓
" 464 ✓
" 465 ✓
" 466 ✓
" 467 ✓
" 468 ✓
" 469 ✓
" 470 ✓
" 471 ✓
" 472 ✓
" 473 ✓
" 474 ✓
" 475 ✓
" 476 ✓
" 477 ✓
" 478 ✓
" 479 ✓
" 480 ✓
" 481 ✓
" 482 ✓
" 483 ✓
" 484 ✓
" 485 ✓
" 486 ✓
664487 ✓
" 488 ✓
" 489 ✓
" 490 ✓
" 491 ✓
" 492 ✓
" 493 ✓
" 494 ✓
" 495 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

SSM 664496 ✓	SSM 664540 ✓	SSM 664578 ✓
" 497 ✓	" 541 ✓	" 579 ✓
" 498 ✓	" 542 ✓	" 580 ✓
" 499 ✓	" 543 ✓	" 581 ✓
" 500 ✓		" 582 ✓
	664546 ✓	" 583 ✓
664508 ✓	" 547 ✓	" 584 ✓
" 509 ✓		" 585 ✓
" 510 ✓	664550 ✓	" 586 ✓
" 511 ✓	" 551 ✓	" 587 ✓
" 512 ✓	" 552 ✓	" 588 ✓
" 513 ✓	" 553 ✓	" 589 ✓
" 514 ✓	" 554 ✓	" 590 ✓
" 515 ✓	" 555 ✓	" 591 ✓
" 516 ✓	" 556 ✓	" 592 ✓
" 517 ✓	" 557 ✓	" 593 ✓
" 518 ✓	" 558 ✓	" 594 ✓
" 519 ✓	" 559 ✓	" 595 ✓
" 520 ✓	" 560 ✓	" 596 ✓
" 521 ✓	" 561 ✓	" 597 ✓
" 522 ✓	" 562 ✓	" 598 ✓
" 523 ✓	" 563 ✓	" 599 ✓
" 524 ✓	" 564 ✓	" 600 ✓
" 525 ✓	" 565 ✓	" 601 ✓
" 526 ✓	" 566 ✓	" 602 ✓
664527 ✓	" 567 ✓	" 603 ✓
" 528 ✓	" 568 ✓	" 604 ✓
" 529 ✓	" 569 ✓	" 605 ✓
" 530 ✓	" 570 ✓	" 606 ✓
" 531 ✓	" 571 ✓	" 607 ✓
" 532 ✓	" 572 ✓	" 608 ✓
" 533 ✓	" 573 ✓	
" 534 ✓	" 574 ✓	664611 ✓
" 535 ✓	" 575 ✓	" 612 ✓
" 536 ✓	" 576 ✓	" 613 ✓
" 537 ✓	" 577 ✓	" 614 ✓

FUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

5.

SSM 664615 ✓	SSM 664654 ✓	SSM 664693 ✓
" 616 ✓	" 655 ✓	" 694 ✓
" 617 ✓	" 656 ✓	" 695 ✓
" 618 ✓	" 657 ✓	" 696 ✓
" 619 ✓	" 658 ✓	" 697 ✓
" 620 ✓	" 659 ✓	" 698 ✓
" 621 ✓	" 660 ✓	" 699 ✓
" 622 ✓	" 661 ✓	" 700 ✓
" 623 ✓	" 662 ✓	" 701 ✓
" 624 ✓	" 663 ✓	" 702 ✓
" 625 ✓	" 664 ✓	
" 626 ✓	" 665 ✓	664708 ✓
" 627 ✓	" 666 ✓	" 709 ✓
" 628 ✓	" 667 ✓	" 710 ✓
" 629 ✓	" 668 ✓	" 711 ✓
" 630 ✓	" 669 ✓	" 712 ✓
" 631 ✓	" 670 ✓	" 713 ✓
" 632 ✓	" 671 ✓	" 714 ✓
" 633 ✓	" 672 ✓	" 715 ✓
" 634 ✓	" 673 ✓	" 716 ✓
" 635 ✓	" 674 ✓	" 717 ✓
" 636 ✓	" 675 ✓	" 718 ✓
" 637 ✓	" 676 ✓	" 719 ✓
" 638 ✓	" 677 ✓	" 720 ✓
" 639 ✓	" 678 ✓	" 721 ✓
" 640 ✓	" 679 ✓	" 722 ✓
" 641 ✓	" 680 ✓	" 723 ✓
" 642 ✓	" 681 ✓	" 724 ✓
" 643 ✓	" 682 ✓	" 725 ✓
" 644 ✓	" 683 ✓	" 726 ✓
" 645 ✓	" 684 ✓	" 727 ✓
" 646 ✓	" 685 ✓	" 728 ✓
" 647 ✓	" 686 ✓	" 729 ✓
" 648 ✓	" 687 ✓	" 730 ✓
" 649 ✓	" 688 ✓	" 731 ✓
" 650 ✓	" 689 ✓	" 732 ✓
" 651 ✓	" 690 ✓	" 733 ✓
" 652 ✓	" 691 ✓	" 734 ✓
" 653 ✓	" 692 ✓	" 735 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

6.

SSM 664736 ✓	SSM 664773 ✓	SSM 664830 ✓
" 737 ✓	" 774 ✓	" 831 ✓
" 738 ✓	" 775 ✓	" 832 ✓
" 739 ✓	" 776 ✓	" 833 ✓
" 740 ✓	" 777 ✓	" 834 ✓
" 741 ✓	" 778 ✓	" 835 ✓
" 742 ✓	" 779 ✓	" 836 ✓
" 743 ✓	" 780 ✓	" 837 ✓
" 744 ✓	" 781 ✓	" 838 ✓
" 745 ✓	" 782 ✓	" 839 ✓
" 746 ✓	" 783 ✓	" 840 ✓
" 747 ✓	" 784 ✓	" 841 ✓
" 748 ✓	" 785 ✓	" 842 ✓
" 749 ✓	" 786 ✓	" 843 ✓
" 750 ✓		" 844 ✓
" 751 ✓	664808 ✓	" 845 ✓
" 752 ✓	" 809 ✓	" 846 ✓
" 753 ✓	" 810 ✓	" 847 ✓
" 754 ✓	" 811 ✓	" 848 ✓
✓ " 755 ✓	" 812 ✓	" 849 ✓
" 756 ✓	" 813 ✓	" 850 ✓
	" 814 ✓	" 851 ✓
664758 ✓	" 815 ✓	" 852 ✓
" 759 ✓	" 816 ✓	" 853 ✓
" 760 ✓	" 817 ✓	" 854 ✓
" 761 ✓	" 818 ✓	" 855 ✓
" 762 ✓	" 819 ✓	" 856 ✓
" 763 ✓	" 820 ✓	" 857 ✓
" 764 ✓	" 821 ✓	" 858 ✓
" 765 ✓	" 822 ✓	" 859 ✓
" 766 ✓	" 823 ✓	" 860 ✓
" 767 ✓	" 824 ✓	" 861 ✓
" 768 ✓	" 825 ✓	" 862 ✓
" 769 ✓	" 826 ✓	" 863 ✓
" 770 ✓	" 827 ✓	" 864 ✓
" 771 ✓	" 828 ✓	" 865 ✓
" 772 ✓	" 829 ✓	" 866 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

7.

SSM 664867 ✓	SSM 664904 ✓	SSM 664940 ✓
" 868 ✓	" 905 ✓	" 941 ✓
" 869 ✓	" 906 ✓	" 942 ✓
" 870 ✓	" 907 ✓	" 943 ✓
" 871 ✓	" 908 ✓	" 944 ✓
" 872 ✓	" 909 ✓	" 945 ✓
" 873 ✓	" 910 ✓	" 946 ✓
" 874 ✓	" 911 ✓	" 947 ✓
" 875 ✓	" 912 ✓	" 948 ✓
" 876 ✓	" 913 ✓	" 949 ✓
" 877 ✓	" 914 ✓	" 950 ✓
" 878 ✓	" 915 ✓	" 951 ✓
" 879 ✓	" 916 ✓	" 952 ✓
" 880 ✓	" 917 ✓	F 953 ✓
" 881 ✓	" 918 ✓	" 954 ✓
" 882 ✓	" 919 ✓	" 955 ✓
" 883 ✓	" 920 ✓	" 956 ✓
" 884 ✓	" 921 ✓	" 957 ✓
" 885 ✓	" 922 ✓	" 958 ✓
" 886 ✓	" 923 ✓	" 959 ✓
" 887 ✓	" 924 ✓	" 960 ✓
" 888 ✓	" 925 ✓	" 961 ✓
" 889 ✓	" 926 ✓	" 962 ✓
" 890 ✓	" 927 ✓	" 963 ✓
" 891 ✓	" 928 ✓	" 964 ✓
" 892 ✓	" 929 ✓	" 965 ✓
" 893 ✓	" 930 ✓	" 966 ✓
" 894 ✓	" 931 ✓	" 967 ✓
" 895 ✓	" 932 ✓	" 968 ✓
664896 ✓	" 933 ✓	" 969 ✓
" 897 ✓	" 934 ✓	" 970 ✓
" 898 ✓	" 935 ✓	" 971 ✓
	" 936 ✓	" 972 ✓
664901 ✓	" 937 ✓	" 973 ✓
" 902 ✓	" 938 ✓	" 974 ✓
" 903 ✓	" 939 ✓	" 975 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

8.

SSM 664976 ✓	SSM 665011 ✓	SSM 665050 ✓
" 977 ✓	" 012 ✓	" 051 ✓
" 978	" 013 ✓	" 052 ✓
" 979 ✓	" 014 ✓	" 053 ✓
" 980 ✓	" 015 ✓	" 054 ✓
" 981 ✓	" 016 ✓	" 055 ✓
" 982 ✓	" 017 ✓	" 056 ✓
" 983 ✓	" 018 ✓	" 057 ✓
" 984 ✓		
" 985 ✓	665020 ✓	665060 ✓
" 986 ✓	" 021 ✓	" 061 ✓
" 987 ✓	" 022 ✓	" 062 ✓
" 988 ✓	" 023 ✓	" 063 ✓
" 989 ✓	" 024 ✓	" 064 ✓
" 990 ✓	" 025 ✓	" 065 ✓
" 991 ✓	" 026 ✓	" 066 ✓
" 992 ✓		" 067 ✓
" 993 ✓	665030 ✓	
" 994 ✓	" 031 ✓	665070 ✓
" 995 ✓	" 032 ✓	" 071 ✓
" 996 ✓	" 033 ✓	" 072 ✓
" 997 ✓	" 034 ✓	" 073 ✓
" 998 ✓	" 035 ✓	" 074 ✓
" 999 ✓	" 036 ✓	" 075 ✓
665000 ✓	" 037 ✓	" 076 ✓
" 001 ✓		" 077 ✓
" 002 ✓	665040 ✓	
" 003 ✓	" 041 ✓	665080 ✓
" 004 ✓	" 042 ✓	" 081 ✓
" 005 ✓	" 043 ✓	" 082 ✓
" 006 ✓	" 044 ✓	" 083 ✓
" 007 ✓	" 045 ✓	" 084 ✓
" 008 ✓	" 046 ✓	" 085 ✓
" 009 ✓	" 047 ✓	" 086 ✓
" 010 ✓		" 087 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

SSM 665090 ✓	SSM 665126 ✓	SSM 665162 ✓
" 091 ✓	" 127 ✓	" 163 ✓
" 092 ✓	" 128 ✓	" 164 ✓
" 093 ✓	" 129 ✓	" 165 ✓
" 094 ✓	" 130 ✓	" 166 ✓
" 095 ✓	" 131 ✓	" 167 ✓
" 096 ✓	" 132 ✓	" 168 ✓
" 097 ✓	" 133 ✓	" 169 ✓
" 098 ✓	" 134 ✓	" 170 ✓
" 099 ✓	" 135 ✓	" 171 ✓
	" 136 ✓	" 172 ✓
665101 ✓	" 137 ✓	" 173 ✓
" 102 ✓	" 138 ✓	" 174 ✓
" 103 ✓	" 139 ✓	" 175 ✓
" 104 ✓	" 140 ✓	" 176 ✓
" 105 ✓	" 141 ✓	" 177 ✓
" 106 ✓	" 142 ✓	" 178 ✓
" 107 ✓	" 143 ✓	" 179 ✓
" 108 ✓	" 144 ✓	" 180 ✓
" 109 ✓	" 145 ✓	" 181 ✓
" 110 ✓	" 146 ✓	" 182 ✓
" 111 ✓	" 147 ✓	" 183 ✓
" 112 ✓	" 148 ✓	" 184 ✓
" 113 ✓	" 149 ✓	" 185 ✓
" 114 ✓	" 150 ✓	" 186 ✓
" 115 ✓	" 151 ✓	" 187 ✓
" 116 ✓	" 152 ✓	" 188 ✓
" 117 ✓	" 153 ✓	" 189 ✓
" 118 ✓	" 154 ✓	" 190 ✓
" 119 ✓	" 155 ✓	" 191 ✓
" 120 ✓	" 156 ✓	" 192 ✓
" 121 ✓	" 157 ✓	" 193 ✓
" 122 ✓	" 158 ✓	" 194 ✓
" 123 ✓	" 159 ✓	" 195 ✓
" 124 ✓	" 160 ✓	" 196 ✓
" 125 ✓	" 161 ✓	" 197 ✓

PUKASKWA RIVER PROPERTY CLAIM LIST - Contd.

10.

SSM 665198 ✓

" 199 ✓

" 200 ✓

" 201 ✓

" 202 ✓

" 203 ✓

" 204 ✓

" 205 ✓

" 206 ✓

" 207 ✓

666672 ✓

" 673 ✓

" 674 ✓

" 675 ✓

" 676 ✓

" 677 ✓

" 678 ✓

" 679 ✓

" 680 ✓

" 681 ✓

" 682 ✓

" 683 ✓

" 684 ✓

" 685 ✓

" 686 ✓

" 687 ✓

" 688 ✓

" 689 ✓

" 690 ✓

" 691 ✓

Total of 95 $\frac{1}{2}$ contiguous claims for approximately 15,395 hectares
(38,040 acres).



Geotechnical
Report
Approval

File **2.5968**
2.5968.

Mining Lands Comments

To: Geophysics *Mr R. Barlow* **MR. R. BARLOW**

Comments

<input checked="" type="checkbox"/> Approved	<input type="checkbox"/> Wish to see again with corrections	Date <i>Jan 7/83</i>	Signature <i>RRLW</i>
--	---	----------------------	-----------------------

To: Geology - Expenditures

Comments

<input type="checkbox"/> Approved	<input type="checkbox"/> Wish to see again with corrections	Date	Signature
-----------------------------------	---	------	-----------

To: Geochemistry

Comments

L.D.

<input type="checkbox"/> Approved	<input type="checkbox"/> Wish to see again with corrections	Date	Signature
-----------------------------------	---	------	-----------

To: Mining Lands Section, Room 6462, Whitney Block. (Tel: 6-1380)

1983 11 07

2.5968

Mrs. M.V. St. Jules
Mining Recorder
Ministry of Natural Resources
875 Queen Street East
P.O. Box 669
Sault Ste. Marie, Ontario
P6A 5N2

Dear Madam:

We have received reports and maps for an Airborne Geophysical (Electromagnetic Magnetometer and VLF) survey submitted on mining claims SSM 619517 et al in the Areas of Pilot Harbour David Lakes.

This material will be examined and assessed and a statement of assessment work credits will be issued.

Yours very truly,


E.F. Anderson
Director
Land Management Branch

Whitney Block, Room 6643
Queen's Park
Toronto, Ontario
M7A 1W3
Phone: (416)965-1380

A. Barr:mc

cc: Midnorth Engineering
Suite 1205
45 Richmond Street West
Toronto, Ontario
M5H 1Z2

cc: Fenton Scott
17 Malabar Place
Don Mills, Ontario
M3B 1A4



DAVID LAKES M-12

HOMER TWP. 54 53 52 51 50 49 48 47 46 45

PIBOT HARBOUR.


DAVID LAKES

2.5968

85° 45'

49 48 47 46 44 43 42 41 40 39

HOMER
PLAN
TWP



PILOT HARBOUR
M-20
1" = 40 CHAINS

Ganley Harbour
Wilderness Area withdrawn
from staking

JL 250 JL 251
JL 252
Le Petite Mort Rocks


UNDER SECTION 42 OF MINING ACT FOR PROPOSED
PUMASKWA NATIONAL PARK
JULY 20/71

2.5968
DAVID LKS M-12
1" = 40 CHAINS

CAMP LAKE

DAVID LAKES
M-12

PILOT HARBOUR




FOR ADDITIONAL

INFORMATION


SEE MAPS:

41N/13NE - 0014 # 1-5



#1
41N/13NE-0014

41N/13NE-0014, #1





42C45E9880 41N13NE-0014 PILOT HARBOUR



Horizontal control based on photo tie-lines
 Average bird height 30 metres
 Line spacing 600 feet


- EM RESPONSE**
 Conductivity thickness in mhos
- ⊙ > 500
 - ⊙ 250 - 500
 - ⊙ 125 - 250
 - ⊙ 60 - 125
 - ⊙ 30 - 60
 - ⊙ 8 - 30
 - ⊙ 4 - 8
 - ⊙ 2 - 4
 - ⊙ < 2
 - ⊙ Inphase response



PROSPECTING GEOPHYSICS LTD.

AIRBORNE ELECTROMAGNETIC SURVEY
 COTTON VALLEY RESOURCES LTD.
 PUKASKWA RIVER CLAIMS
 ONTARIO


SCALE 1/15,840




DATE: February, March 1983
 N.T.S. No: 41N, 42C
 MAP No: I

▼ AERODAT LIMITED

41N/13 NE-0014, #2



41N/13NE-0014, #3




PROSPECTING GEOPHYSICS LTD.
AIRBORNE ELECTROMAGNETIC SURVEY PROFILES
 COTTON VALLEY RESOURCES LTD.
 PUKASKWA RIVER CLAIMS
 ONTARIO

SCALE 1/5,840
 1/2 Mile
 1 Kilometre


DATE February, March 1983
 N.T.S. No. 41N, 42C
 MAP No. 2

AERODAT LIMITED



LEGEND
 100 gamma
 50 gamma
 10 gamma

41N13NE-0014, #4



PROSPECTING GEOPHYSICS LTD.

TOTAL FIELD MAGNETIC MAP
 COTTON VALLEY RESOURCES LTD.
 PUKASKWA RIVER CLAIMS
 ONTARIO

SCALE 1/15,840 1/2 Mile
 0 1 kilometre

DATE February, March 1983
 N.T.S. No. 41N, 42C
 MAP No. 3


AERODAT LIMITED



LEGEND

- 50 %
- 10 %
- 2 %

41N/13NE-0014, #5



PROSPECTING GEOPHYSICS LTD.
 VLF-EM
 NAA (MAINE) 17.8 KHz.
 COTTON VALLEY RESOURCES LTD.
 PUKASKWA RIVER CLAIMS
 ONTARIO

SCALE 1/15,840

DATE February, March 1983
 N.T.S. No. 41N, 42C
 MAP No. 4

▼ AERODAT LIMITED